imagePROGRAF GP-300 STAND OUT FROM THE CROWD WITH VIBRANT, PREMIUM QUALITY POSTERS

A compact, large format printer expertly designed for high impact poster design, POS and signage with vibrant colours, ideal for stand-out retail and hospitality marketing.





Vibrant neon colours

Stand out from other stores with the vibrant fluorescent pink ink, adding neon expression to your poster design for an eye-catching finish

Simple design software

Embrace the power of customisation with easy-to-use design software, including new PosterArtist 3.4 with new templates and stock photo resource

Free-size borderless printing

Free-size borderless printing makes poster production easier than ever, with high-precision paper edge detection supporting prints of all sizes

Direct to print

Built-in HDD allows to reprint saved data easily, plus JPG/PDF images can be printed directly from a USB memory

Compact design

Maximise available office space with a small footprint printer that fits flat against the wall to offer full front usability, perfect for smaller offices

Security assured

Have confidence in your data security with pin-accessed Security Print feature, plus built-in secure file erasure function, preventing information leakage or loss



PRODUCT RANGE



imagePROGRAF GP-200



imagePROGRAF GP-4000



imagePROGRAF GP-2000







TECHNICAL SPECIFICATIONS

6 Colour 36"

2.400 x 1.200 dpi

imagePROGRAF **GP-300**

Roll Paper : 1 roll Cut Sheet : 1 sheet

TECHNOLOGY Printer Type Print Technology

Print Resolution Number of Nozzles

Line Accuracy

Nozzle Pitch

Ink Droplet Size Ink Capacity

Ink Type OS Compatability

Printer Languages Standard Interfaces

MEMORY

- Standard memory
- Hard Drive

PRINTING SPEED Poster:

Plain Paper (A0)

Heavy coated Paper (A0) Glossy photo Paper (A0)

MEDIA HANDLING

Media Feed and Output

Media Width

Media Thickness Minimum Printable Length

Maximum Printable Length

Maximum Media Roli Diameter Media Core Size Margins Recommended area

Margins Printable area

each ±0.% or less User adjustments necessary. Printing environment and media must match those used for the adjustments. CAD paper required: Plain paper, CAD tracing paper, coated paper, CAD translucent matte film only 1,200 dpi x 2 includes Non-firing nozzle detection and compensation system minimum 5 pl per colour Bundled Starter Ink: 90 ml (MBK, BK, C, M, Y, FP) Sales Ink: 130 ml/300 ml Pigment inks : 6 colour MBK/BK/C/M/Y/FP Microsoft Windows 32 Bit : 7, 8.1, 10 Microsoft Windows 64 Bit : 7, 8.1, 10, Windows Server 2008R2, 2012, 2012R2, 2016, 2019 Apple Macintosh : macOS 10.13.6 - macOS 11 PDF (Ver.1.7), JPEG (Ver. JFIF 1.02) USB A Port : USB Memory Direct Print for JPEG/PDF files USB B Port : Built-in Hi-Speed USB Ethernet : IEEE 802.3 10base-T, IEEE 802.3u 100base-T/ Auto-Negotiation, IEEE 802.3ab 1000base-T/ Auto-Negotiation, IEEE 802.3x Full Duplex Wireless LAN : IEEE802.1ln/IEEE802.1lg/IEEE802.1lb *Please refer to user manual how to activate

0:44 (Fast) 1:18 (Standard)

Roll Paper : One Roll, Upper-loading, Front Output Cut Sheet : Upper-loading, Front Output (Manual feed using media locking lever) Roll paper: Top: 20 mm, Bottom: 3 mm, Side: 3 mm Cut sheet: Top: 20 mm, Bottom: 20 mm, Side: 3 mm

Roll paper : Top: 3 mm, Bottom: 3 mm, Side: 3 mm Roll paper (borderless print) : Top: 0 mm, Bottom: 0 mm, Side: 0 mm Cut sheet : Top: 3 mm, Bottom: 20 mm, Side: 3 mm

Borderless Printing Width (Roll Only) Cart Street, 1 Juster, Canon Bubblejet on Demand 6 colours integrated type (6 chips per print head x 1 print head) Total : 15,360 nozzles MBK, BK, C, M, Y, FP : 2,560 nozzles Maximum number of delivered Standard position of the basket : 1 sheet prints DIMENSIONS AND WEIGHT 1289 x 870 x 1060 mm (Basket Open) 1289 x 757 x 1060 mm (Basket Closed) 59 kg (Main Unit + 5tand + Basket, including Roll Holder Set, excluding ink and print head) Physical Dimensions WxDxH (mm) and Weight (Kg) Packaged Dimensions WxDxH (mm) and Weight (Kg) Printer (Main unit with pallet) : 1462 x 913 x 709 mm 79 kg Stand + Basket : 1362 x 824 x 268 mm 17 kg POWER AND OPERATING REQUIREMENTS Power Supply AC 100-240V (50-60Hz) Operation : 74 W or less Sleep mode : 2.1 W or less Default setting for the time to enter the Sleep mode : Power Consumption Approx. 5 Minutes Power off: 0.3 W or less Temperature : 15~30°c, Humidity : 10~80% RH (no dew condensation) Operating Environment Accoustic Noise Pressure Operation : 49 dB (A) (Plain paper, Standard mode, Poster) (Measured on ISO7779 standard) Standby : 35 dB (A) or less Dower (Power/Pressure) Power Operation : 6.7 Bels (Plain paper, Standard mode, Poster) (Measured on ISO7779 standard) Europe : CE mark Other Countries : CB certfication Regulations Enviroment Certificates TUV. CB WHAT'S INCLUDED What's In the Box? Printer, 1 print head, 1 roll holder (spool), 3 inch paper core attachment, Power Cable, 1 set of starter ink tanks, Set up guide, Printer Stand Setup Guide, Quick Guide, Safety/ Standard Environment leaflet, User software CD-ROM (Win), PosterArtist Lite CD-ROM, EU Biocide Sheet, Important Information Sheet imagePROGRAF GP Printer Driver and PosterArtist Lite Other software available as Download from Web Software Included software available as Download from Web OPTIONS Optional Items 2/3" Roll Holder : RH2-35

> CONSUMABLES User Replaceable Items

Media Feed Capacity

Disclaimer

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.^m and * All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Ink Tank : PEI-120 (130ml), PEI-320 (300ml) Print Head : PE-07 Cutter Blade : CT-08 Maintenance Cartridge : MC-31

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.







Canon Inc. canon com **Canon Europe**

canon-europe.com English edition © Canon Europa N.V.,2021



wireless LAN 2GB Expansion slot : No 500GB

1:41 (Fast) 2:36 (Standard) 6:19 (Standard) 9:41 (High Quality)

Roll paper : 203.2 mm - 917 mm Cut sheet : 203.2 mm - 917 mm Roll/Cut : 0.07 mm - 0.8 mm Roll paper : 203.2 mm Cut sheet : 279.4 mm Roll paper : 18 m (Varies according to the OS and application) Cut sheet : 1.6 m 150 mm Internal diameter of roll core : 2"/3"