

imagePROGRAF PRO-2000

Large format reliable and consistent print for photography, fine art and proofing.

For the very best photographic print quality, the imagePROGRAF PRO-2000 can produce images up to 24" with the best print quality, outstanding speed and reliability.



*2nd roll unit and printer stand are optional

- Using LUCIA PRO 12 inks, colours are richer and blacks are deeper, producing prints that are faithful to your images
- A new 1.28" wide print head enables faster printing while maintaining high print quality.
- Optional dual roll unit supports continuous paper feed or automatic take-up of the printed output.
- An attractive black body hardware design with an accentuated red line denoting the link with Canon EOS digital cameras.
- Ergonomic design with a flat top surface for print checking and 3.5" colour LCD touch screen operation panel.
- Fast and easy printing directly for PDF and JPEG file formats from USB memory stick.
- Wi-Fi functionality for easy connection and quick setup to wireless networks.
- Guaranteed colour consistency between jobs and different production sites.
- High-capacity "hot swap" ink tanks for uninterrupted printing.
- The Print Studio Pro plug-in lets you print effortlessly from professional editing software such as Adobe Lightroom®, Adobe Photoshop® and Canon's Digital Photo Professional.



Canon

imagePROGRAF PRO-2000

TECHNOLOGY

Printer Type

12 Colour 24"/610mm

Print Technology

Canon Bubblejet on Demand 12 colours integrated type (12 chips per print head x 1 print head)

Number of Nozzles

18,432 nozzles (1536 nozzles x 12 colour)

Print Resolution

2,400 dpi x 1200 dpi

Nozzle Pitch

600 dpi x 2 includes Non-firing nozzle detection and compensation system

Line Accuracy

±0.1% or less
User adjustments necessary. Printing environment and media must match those used for the adjustments.
CAD paper required: Plain paper, CAD tracing paper, coated paper, CAD translucent matte film only

Ink Droplet Size

minimum 4 pl per colour

Ink Capacity

Sales Ink: 160ml/330ml/700ml
Bundled Starter Ink: 160ml

Ink Type

Pigment inks - Black, Matte Black, Cyan, Magenta, Yellow, Photo Cyan, Photo Magenta, Grey, Photo Grey, Red, Blue, Chroma Optimiser

OS Compatibility

Microsoft Windows 32 Bit: Vista, 7, 8, 8.1, 10, Server 2008, 64 Bit: Vista, 7, 8, 8.1, 10, Server 2008/R2, Server 2012/R2
Apple Macintosh: OSX 10.7.5 - 10.11

Printer Languages

SG Raster (Swift Graphic Raster)

Standard Interfaces

USB A Port: USB Memory Direct Print for JPEG/PDF files
USB B Port: Built-in Hi-Speed USB 2.0
Ethernet: 10/100/1000 base-T
Wireless LAN: IEEE802.11n/IEEE802.11g/IEEE802.11b

MEMORY

Standard memory

1 GB

Hard Drive

320 GB

PRINTING PAGE SIZE/ PRINT SPEED

Plain Paper

Coated Paper

Photo Glossy Paper

MEDIA HANDLING

Media Feed and Output

Roll Paper: One Roll, Front-loading, Front Output
Optional Roll Paper: One Roll, Front-loading, Front Output
Cut Sheet: Front-loading, Front Output (Manual feed using media locking lever)

Media Width

Roll paper: 203.2 - 610 mm
Cut sheet: 203.2 - 610 mm

Media Thickness

Roll/Cut: 0.07 - 0.8 mm

Minimum Printable Length

203.2 mm

Maximum Printable Length

Roll paper: 18 m (Varies according to the OS and application)
Cut sheet: 1.6 m

Maximum Media Roll Diameter

170 mm

Media Core Size

Internal diameter of roll core: 2"/3"

Margins Recommended area

Roll paper: Top: 20 mm, Bottom: 3 mm, Side: 3 mm
Cut sheet: Top: 20 mm, Bottom: 20 mm, Side: 3 mm

Margins Printable area

Roll paper: Top: 3 mm, Bottom: 3 mm, Side: 3 mm
Roll paper (borderless): Top: 0 mm, Bottom: 0 mm, Side: 0 mm
Cut sheet: Top: 3 mm, Bottom: 20 mm, Side: 3 mm

Media Feed Capacity

Roll Paper: One roll. If second option is added then automatic switching is possible

Media Take-up roll unit

Optional - Dual direction roll take up unit allowing print surface to be wound inside or outside of the roll

Borderless Printing Width (Roll Only)

515 mm (JIS B2), 594 mm (ISO A1), 10", 14", 17", 24", 257 mm (JIS B4)*, 297 mm (ISO A3)*, 329 mm (ISO A3+)*, 420 mm (ISO A2)*, 8", 16", 300 mm*

*Some environmental conditions may not produce the desired result

Maximum number of delivered prints

Standard position: 1 sheet
Flat position: A2 landscape, glossy paper less than 10 sheets, Coated paper less than 20 sheets (excludes strong curled condition)

DIMENSIONS AND WEIGHT

Physical Dimensions

WxDxH (mm) & Weight (Kg)

1110 x 984 x 1168 (Basket Opened)

1110 x 766 x 1168 (Basket Closed)

Weight: approx 101 kg (including Roll Holder Set, excluding ink and print heads)

Packaged Dimensions

WxDxH (mm) & Weight (Kg)

Printer (Main unit with pallet): 1322 mm x 900 mm x 1035 mm

Weight: approx: 122 kg

Stand/Basket: 1109 mm x 795 mm x 217mm,

Weight: approx: 22 kg

POWER AND OPERATING REQUIREMENTS

Power Supply

AC 100-240V (50-60Hz)

Power Consumption

Operation: 88 W or less

Standby: 1.8 W or less

Power off: 0.5 W or less

Operating Environment

Temperature: 15-30°C, Humidity: 10-80% RH (no dew condensation)

Acoustic Noise (Power/Pressure)

Operation: TBD dB (A) (Glossy paper, Print priority: Standard)

Standby: TBD dB (A) or less

Operation: TBD Belts or less

(Glossy paper, Image, Print priority: Standard) (Measured on ISO7779 standard)

Regulations

Europe: CE mark, Germany: TUV mark, Russia: EAC, Other countries: CB certification

Environment Certificates

International Energy Star Program (WW), RoHS

WHAT'S INCLUDED

What's in the Box?

Printer, 1x print head, 3" paper core attachment, EU & UK Power Cable, 1 set of starter ink tanks, Set up guide, Safety/Standard Environment leaflet, User software CD-ROM (OSX/Windows), PosterArtist Lite CD-ROM, EU Biocide Sheet, Eurasian Economic Union Sheet, Important Information Sheet, Quick Guide and Printhead Alignment Sheet

Software Included

imagePROGRAF PRO Printer Driver, Print Plug-In for Office, Quick Utility Toolbox and PosterArtist Lite
Other software available as Download from Web.

WHAT'S INCLUDED

Optional Items

Printer Stand: SD-21

Roll Unit: RU-21

2/3" Roll Holder: RH2-27

CONSUMABLES

User Replaceable Items

Ink Tank: PFI-1100(160ml), PFI-1300(330ml), PFI-1700(700ml)

Print Head: PF-10

Cutter Blade: CT-07

Maintenance Cartridge: MC-30



Crystal-fidelity



Canon Inc.
canon.com

Canon Europe
canon-europe.com

English edition
© Canon Europa N.V., 2016