## imagePROGRAF PRO-4000S

Designed for high volume production, advertisements, graphics, posters and proofing. The imagePROGRAF PRO-4000S is designed to deliver the high volume, outstanding quality, large format (up to 44") printing you need, as quickly as possible, time and again, with complete reliability.







- Outstanding LUCIA PRO 8-colour quality, at impressive speed, with up to 44" large format production output.
- A new 1.28" wide print head enables faster printing while maintaining high print quality.
- Optional dual roll unit supports continuous paper feeding or automatic take-up of printer output.
- Visually attractive and distinctive, black body hardware design.
- Ergonomic design with a flat top surface for print checking and 3.5" LCD colour touch screen operation panel.

- Fast and easy printing of PDF and JPEG files directly from USB memory stick.
- Wi-Fi connectivity for easy connection and quick setup to wireless networks.
- High-capacity "hot swap" ink tanks for uninterrupted printing.
- Guaranteed colour consistency between jobs and different production sites.
- The Print Studio Pro plug-in lets you print effortlessly from professional editing software such as Adobe Lightroom®, Adobe Photoshop® and Canon's Digital Photo Professional.



## Technical Specifications

8 Colour 44"/1118mm

2400 x1200 dpi

## imagePROGRAF PRO-4000S

TECHNOLOGY Printer Type Print Technology

Number of Nozzles

Nozzle Pitch

Line Accuracy

Ink Droplet Size Ink Capacity

Ink Type

OS Compatability

Printer Languages Standard Interfaces

MEMORY

Standard memory Hard Drive

PRINTING PAGE SIZE/ PRINT SPEED Plain Paper Coated Paper Photo Glossy Paper

## MEDIA HANDLING Media Feed and Output

Media Width

Media Thickness Minimum Printable Length Maximum Printable Length

Maximum Media Roll Diameter Media Core Size Margins Recommended area 170 mm

Margins Printable area

compensation system

 ±0.1% or less
 User adjustments necessary. Printing environment and media must match those used for the adjustments.
 CAD paper required. Plain paper, CAD tracing paper, coated paper, CAD translucent matte film only
 minimum 4pl per colour
 Saless use: 160-ml(330-ml/700-ml)
 Starter use: 330ml (C, M, Y, MBk), 190ml(PC, PM, Bk, GY)
 Pigment inks - Black, Matte Black, Cyan, Magenta, Yellow, Photo Cyan, Photo Magenta, Grey
 Microsoft Windows 32 Bit: Vista, 7, 8, 8.1, 10, Server 2008, 64 Bit: Vista, 7, 8, 8.1, 10, Server 2008/R2, Server 2012/R2
 Apple Macintosti OSX 10.7.5 - 10.11
 SG Raster (Swift Graphic Raster)
 USB A Port: USB Memory Direct Print for JPEG/PDF files
 USB P Dert: Built-in Hi-Speed USB 2.0
 Ethernet: 10/100/1000 base-T
 Wireless LAN: IEEE802.11n/IEEE802.11g/IEEE802.11b

 1 GB
 320GB
 Roll Paper: One Roll, Front-loading, Front Output Optional Roll Paper: One Roll, Front-loading, Front Output Cut Sheet: Front-loading, Front Output Cut Sheet: Ton-Loading, Front Output (Manual feed using media locking lever)
 Roll paper: 20.3 - 1118 mm
 Cut sheet: 20.3 - 118 mm
 Roll/Cut: 0.07 - 0.8 mm
 203.2 mm
 Roll paper: 18 m (Varies according to the OS and application)
 Cut sheet: 18 m (Varies according to the OS and application)

Canon Bubblejet on Demand 8 colours integrated type (12 chips per print head x 1 print head)

600 dpi x 2 includes Non-firing nozzle detection and

\*The four key colours (C, M, Y, MBk) are arranged symmetrically on the print head

18,432 nozzles (1536 nozzles x 12 colour)\*

Internal diameter of roll core: 2"/3" Roll paper: Top: 20 mm, Bottom: 3 mm, Side: 3 mm Cut sheet: Top: 20 mm, Bottom: 20 mm, Side: 3 mm Roll paper: Top: 3 mm, Bottom: 3 mm, Side: 3 mm Roll paper (borderles): Top: 0 mm, Bottom: 0 mm, Side: 0 mm Cut sheet: Top: 3 mm, Bottom: 20 mm, Side: 3 mm Media Feed Capacity

Media Take-up roll unit Borderless Printing Width (Roll Only)

. . . .

DIMENSIONS AND WEIGHT

Maximum number of delivered prints

Physical Dimensions WxDxH (mm) & Weight (Kg)

Packaged Dimensions WxDxH (mm) & Weight (Kg) Printer: (M Weight ap

POWER AND OPERATING REQUIREMENTS

Power Supply Power Consumption

Operating Environment

Accoustic Noise (Power/ Pressure)

Regulations

Enviroment Certificates

WHAT'S INCLUDED What's in the Box?

Software Included

OPTIONS Optional Items

CONSUMABLES User Replaceable Items

Roll Paper: One roll. If second option is added then automatic switching is possible Cut Sheet: 1 sheet

Optional - Dual direction roll take up unit allowing print surface to be wound inside or outside of the roll

515 mm(JIS B2), 728 mm(JIS B1), 1030 mm(JIS B0), 594 mm(JSO A1), 841 mm(JSO A0), 10°, 14″, 17″, 24″, 36″, 42″, 44″, 257 mm(JIS B4)\*, 297 mm(JSO A3)\*, 329 mm(JSO A3+)\*, 420 mm(JSO A2)\*, 8″\*, 16″\*, 30″\*, 300 mm\*

\*Some environmental conditions may not produce the desired result. Standard position: 1 sheet

Standard position: 1 sheet Flat position: A2 landscape, glossy paper less than 10 sheets, Coated paper less than 20 sheets (excludes strong curled condition)

1593 x 984 x 1168 mm (Basket Opened) 1593 x 766 x 1168 mm (Basket Closed) Weight approx : 121 kg (including Roll Holder Set, excluding ink and print heads)

Printer: (Main unit and stand with pallet): 1818 x 913 x 1012 mm, Weight approx: 164 kg

AC 100-240V (50-60Hz) Operation: 107 W or less Standby: 1.8 W or less Power off: 0.5 W or less

Temperature: 15-30°c, Humidity: 10-80% RH (no dew condensation)

Operation: TBD dB (A) (Glossy paper, Print priority: Standard) Standby: TBD dB (A) or less Operation: TBD Bels or less (Glossy paper, Image, Print priority: Standard) (Measured on ISO7779 standard)

Europe: CE mark, Germany: TUV mark, Russia: EAC, Other countries: CB certification

International Energy Star Program (WW), RoHS

Printer, 1x print head, 3" paper core attachment, EU & UK Power Cable, 1 set of starter ink tanks, Set up guide, Safety/ Standard Environment leaflet, User software CD-ROM (OSX/ Windows), PosterArtist Lite CD-ROM, EU Biocide Sheet, Eurasian Economic Union Sheet, Important Information Sheet, Quick Guide and Printhead Alignment Sheet

imagePROGRAF PRO Printer Driver, Print Plug-In for Office, Quick Utility Toolbox and PosterArtist Lite Other software available as Download from Web.

Roll Unit: RU-41 2/3" Roll Holder: RH2-45

Ink Tank: PFI-1100(160ml), PFI-1300(330ml), PFI-1700(700ml) Print Head: PF-10 Cutter Blade: CT-07 Maintenance Cartridge: MC-30

**PRO** ink



**Crystal-fidelity** 



Canon Inc. canon.com Canon Europe canon-europe.com English edition © Canon Europa N.V.,2016