



imagePROGRAF TM-240

PERFORMANCE REIMAGINED

Reimagine printing performance with the sustainable 24" imagePROGRAF TM-240, offering less noise printing, more intuitive functionality and brilliant image quality. Seamlessly produce sharp, crisp lines and vivid red colour for eye-catching marketing materials and accurate CAD prints for AEC offices, retail and education.

- **Enhanced professional quality**
The new magenta ink produces a more brilliant red and stable image enhancements mean crisper lines. Print vivid and accurate CAD drawings, posters, educational materials and more
- **Intuitive functionality**
Functional design with a 4.3" touch screen panel displaying intuitive instructions and important information, like media type, remaining media and ink amount. Roll paper can be replaced with ease on the flat-top cover
- **Reliable productivity**
Productivity that you can count on, with reliable performance, faster processing time and a quick return from sleep mode. Save time trimming excess margins with borderless print, giving full bleed images of any size, straight from the device
- **Improved sustainability**
Environmentally conscious EPEAT Gold* rated device for low energy consumption, with power reduction during standby and packaging free from polystyrene foam. Less noise printing makes it ideal for quiet offices

*EPEAT Gold registered in the U.S.

Canon

TECHNICAL SPECIFICATIONS

imagePROGRAF™-240

PRINTER TECHNOLOGY		Margins Printable area	Roll paper: Top: 3mm, Bottom: 3mm, Side: 3mm Roll paper (borderless): Top: 0mm, Bottom: 0mm, Side: 0mm Cut sheet (AppleAirPrint): Top: 3mm, Bottom: 12.7mm, Side: 3mm Cut sheet (Others): Top: 3mm, Bottom: 20mm, Side: 3mm
Printer Type	5 Colours 24"	Media Feed Capacity	Roll Paper: One roll Cut Sheet: 1 sheet
Print Technology	Canon Bubblejet on Demand 6 colours integrated type (6 chips per print head x 1 print head)	Borderless Printing Width (Roll Only)	[Recommended] 515mm(JIS B2), 728mm(JIS B1), 594mm (ISO A1), 10", 14", 17", 24"
Print Resolution	2,400 x 1,200 dpi	Maximum number of delivered prints	[Printable] 257mm(JIS B4), 297mm (ISO A3), 329mm (ISO A3+), 420mm(ISO A2), 515mm (JIS B3), 8", 12", 15", 16", 18", 20", 22", 300mm, 500mm, 600mm
Number of Nozzles	Total : 15360 nozzles MBK : 5120 nozzles BK, C, M, Y: 2560 nozzles each	POWER AND OPERATING REQUIREMENTS	Other than above, free size borderless printing is supported on only roll paper by user definition
Line Accuracy	±0.1% or less User adjustments necessary. Printing environment and media must match those used for the adjustments.	Power Supply	Standard position - 1 sheet
Nozzle Pitch	1,200 dpi x 2 lines	Power Consumption	AC 100-240V (50-60Hz) Operation: 59W or less Sleep mode: 2.2W or less Default setting for the time to enter the Sleep mode: Approx. 5 minutes Power off: 0.1W or less
Ink Droplet Size	minimum 5pl per colour	Operating Environment	Temperature: 15-30°C, Humidity: 10-80% RH (no dew condensation)
Ink Capacity	Bundled Starter Ink: 300ml (80ml for MBK, 55mlx4 for BK, C, M, Y) Sales Ink: 55ml (MBK, BK, C, M, Y)	Acoustic Noise (Power/Pressure)	Operation: Approx. 39dB(A) (Standard Plain Paper, Standard mode, Line Drawing/Text mode) (Measured based on ISO7779 standard) Standby: 35 dB(A) or less
Ink Type	Pigment inks : 5 colours MBK/BK/C/M/Y	Regulations	CE mark, UKCA mark
OS Compatibility	32 Bit: Windows 7, Windows 8.1, Windows 10 64 Bit: Windows 7, Windows 8.1, Windows 10, Windows 11, Windows Server 2008R2, 2012, 2012R2, 2016, 2019, 2022 Apple Macintosh: macOS 10.15.7-macOS 13	Environment Certificates	CB certification, EPEAT GOLD ¹⁾
Others supported job submission protocol	Apple AirPrint	DIMENSIONS AND WEIGHT	
Printer Languages	HP-GL/2, HP RTL, JPEG (Ver. JFIF 1.02), CALS G4 (submission via FTP only)	Physical Dimensions and Weight	W x D x H Main unit + Stand + Basket (SD-24) 978 x 868 x 1060 mm (Operation panel is not tilted up/Basket Opened) 978 x 756 x 1060 mm (Operation panel is not tilted up/Basket Closed) 50.9 kg (including Roll Holder Set, excluding ink and print head)
Standard Interfaces	USB A Port: N/A USB B Port: Hi-Speed USB Ethernet: IEEE802.3ab(1000Base-T), IEEE802.3u(100BASE-TX)/IEEE802.3 (10BASE-T) Wireless LAN: IEEE802.11n/IEEE802.11g/IEEE802.11b *Please refer to user manual how to activate/deactivate the wireless LAN	Packaged Dimensions and Weight	Printer (Main unit with pallet): 1152 x 912 x 679 mm, 71kg Stand + Basket (SD-24): 1058 x 826 x 270 mm, 20kg
MEMORY		WHAT'S INCLUDED	
Standard Memory	2GB Expansion slot : No	What's in the Box?	Printer, 1 Print head, Power Cable, 1 Set of starter ink tanks, Installation Guide, Safety/Standard Environment leaflet, LFP Eur Address Sheet, Important Information Sheet, Notice for PosterArtist WEB
Hard Drive	N/A	Software included	Software available as Download from Web
PRINTING SPEED		OPTIONS	
CAD Drawing		Optional Items	Stand Basket (Simple Basket): SD-24 2"/3" Roll Holder: RH2-28 IC Card Reader Holder: RA-02
Plain paper (A1):	0:23 (Fast Economy Model) 0:25 (Fast) 0:51 (Standard)	CONSUMABLES	
Poster:		User Replaceable Items	Ink Tank: M: PFI-031(55ml), MBK/BK/C/Y:PFI-030(55ml) Print Head: PF-06 Cutter Blade: CT-08 Maintenance Cartridge: MC-31
Plain Paper (A1):	0:25 (Fast Economy Model) 0:25 (Fast) 0:49 (Standard)		
Heavy coated paper (A1):	0:56 (Fast) 1:45 (Standard)		
MEDIA HANDLING			
Media Feed and Output	Roll Paper : One Roll, Upper-loading, Front Output Cut Sheet : Upper-loading, Front Output (Manual feed using media locking lever)		
Media Width	Roll paper: 203.2 - 610mm Cut sheet: 210 - 610mm		
Media Thickness	Roll/Cut : 0.07mm - 0.8mm		
Minimum Printable Length	Roll paper: 203.2mm Cut sheet: 279.4mm		
Maximum Printable Length	Roll paper : 18m (varies according to the OS and application) Cut sheet : 1.6m		
Maximum Media Roll Diameter	150 mm		
Media Core Size	Internal diameter of roll core: 2"/3" (Optional)		
Margins Recommended area	Roll paper: Top: 20mm, Bottom: 3mm, Side: 3mm Cut sheet(AppleAirPrint): Top: 20mm, Bottom: 31mm, Side: 3mm Cut sheet (Others): Top: 20mm, Bottom:20mm, Side:3mm		

¹⁾ EPEAT Gold registered in the U.S.

Disclaimer

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ®: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.



Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
© Canon Europa N.V., 2023