



## imagePROGRAF TM-350 / TM-355

# PERFORMANCE REIMAGINED

Elevate printing experiences with enhanced productivity, intuitive functionality and professional image quality from a sustainable device. The 36" printer can seamlessly create accurate CAD prints with sharp lines and eye-catching marketing materials, for corporate and sizable AEC offices and the retail and education sector.

- **Professional printing quality**  
Use stable image enhancements to create sharp, crisp lines and new magenta ink for vivid red colour. As a result, you'll produce vivid and accurate CAD drawings, posters and educational materials
- **Enhanced productivity**  
Produce A1 CAD prints in just 17 seconds, or A1 posters in 22 seconds. Save time trimming excess margins with borderless prints of any sizes and easily meet higher print demand with larger ink tanks, quick processing time and a fast return from sleep mode
- **Intuitive functionality**  
Follow easy instructions and take in important information like media type, remaining media and ink amount on a 4.3" touch screen panel. Save time by setting roll paper with quick access through a flat-top cover
- **Improved sustainability**  
Environmentally conscious EPEAT Gold\* rated device for low energy consumption, with power reduction during standby and packaging free from polystyrene foam. Less noise printing makes it ideal for quiet offices

\* EPEAT Gold registered in the U.S.

# Canon

PRINTER TECHNOLOGY	TM-350	TM-355	TM-350	TM-355
<b>Printer Type</b>	5 Colours 36"		<b>Margins Printable area</b>	
<b>Print Technology</b>	Canon Bubblejet on Demand 6 colours integrated type (6 chips per print head x 1 print head)		Roll paper: Top: 3mm, Bottom: 3mm, Side: 3mm Roll paper (borderless): Top: 0mm, Bottom: 0mm, Side: 0mm Cut sheet (AppleAirPrint): Top: 3mm, Bottom: 12.7mm, Side: 3mm Cut sheet (Others): Top: 3mm, Bottom: 20mm, Side: 3mm	
<b>Print Resolution</b>	2,400 x 1,200 dpi		<b>Media Feed Capacity</b>	
<b>Number of Nozzles</b>	Total : 15360 nozzles MBK : 5120 nozzles BK, C, M, Y: 2560 nozzles each		Roll Paper: One roll Cut Sheet: 1 sheet	
<b>Line Accuracy</b>	±0.1% or less User adjustments necessary. Printing environment and media must match those used for the adjustments.		<b>Borderless Printing Width (Roll Only)</b>	
<b>Nozzle Pitch</b>	1,200 dpi x 2 lines		[Recommended] 515mm(JIS B2), 728mm(JIS B1), 594mm(ISO A1), 841mm(ISO A0), 10", 14", 17", 24", 36"	
<b>Ink Droplet Size</b>	minimum 5pl per colour		[Printable] 257mm(JIS B4), 297mm(ISO A3), 329mm(ISO A3+), 420mm(ISO A2), 515mm(JIS B3), 8", 12", 15", 16", 18", 20", 22", 30", 34", 300mm, 500mm, 600mm, 800mm	
<b>Ink Capacity</b>	Bundled Starter Ink: 490ml (130ml for MBK, 90mlx4 for BK, C, M, Y) Sales Ink: 300 / 130ml (MBK, BK, C, M, Y) Pigment inks : 5 colours MBK/BK/C/M/Y		Other than above, free size borderless printing is supported on only roll paper by user definition	
<b>Ink Type</b>	32 Bit: Windows7, Windows 8.1, Windows 10 64 Bit: Windows 7, Windows 8.1, Windows 10, Windows 11, Windows Server 2008R2, 2012, 2012R2, 2016, 2019, 2022 Apple Macintosh: macOS 10.15.7-macOS 13		<b>Maximum number of delivered prints</b>	
<b>OS Compatibility</b>	Apple AirPrint		Standard position: 1 sheet Folding position: Plain paper 20 sheets on A1 portrait / A0 portrait Flat position: Plain paper 20 sheets on A2 landscape / A1 landscape (exclude strong curled position)	
<b>Others supported job submission protocol</b>			<b>POWER AND OPERATING REQUIREMENTS</b>	
<b>Printer Languages</b>	HP-GL/2, HP RTL, JPEG (Ver. JFIF 1.02), CALS G4 (submission via FTP only)	HP-GL/2, HP RTL, PDF (Ver. JFIF 1.02), CALS G4 (submission via FTP only)	<b>Power Supply</b>	
<b>Standard Interfaces</b>	USB A Port: N/A  USB B Port: Hi-Speed USB Ethernet: IEEE802.3ab(1000base-T), IEEE802.3u(100BASE-TX)/IEEE802.3(10BASE-T) Wireless LAN: IEEE802.11n/IEEE802.11g/IEEE802.11b	USB A Port: USB Memory (Direct Print)	AC 100-240V (50-60Hz)	
	*Please refer to user manual how to activate/deactivate the wireless LAN		<b>Power Consumption</b>	
<b>MEMORY</b>			Operation: 65W or less Sleep mode: 2.2W Default setting for the time to enter the Sleep mode: Approx. 5 minutes Power off: 0.1W or less	
<b>Standard memory</b>	2GB Expansion slot: No	128GB (Physical memory 2GB) Expansion slot : No	Operation: 69W or less Sleep mode: 2.2W Default setting for the time to enter the Sleep mode: Approx. 5 minutes Power off: 0.1W or less	
<b>Hard Drive</b>	N/A	500GB (Encrypted)	Temperature: 15-30°C, Humidity: 10-80% RH (no dew condensation)	
<b>PRINTING SPEED</b>			Operation: Approx. 41dB(A) (Standard Plain Paper, Standard mode, Line Drawing/Text mode) (Measured based on ISO7779 standard) Standby: 35 dB(A) or less Operation: 6.2 Bels or less (Standard Plain Paper, Standard mode, Line Drawing/Text mode) (Measured based on ISO7779 standard)	
<b>CAD Drawing</b>			<b>Regulations</b>	
<b>Plain Paper (A1)</b>	0:17 (Fast Economy Mode) 3.2ppm		<b>Environment Certificates</b>	
<b>Plain Paper (A0)</b>	0:32 (Fast Economy Model) 0:41 (Fast) 1:08 (Standard)		CE mark, UKCA mark CB certification, EPEAT GOLD <sup>1</sup>	
<b>Poster:</b>			<b>DIMENSIONS AND WEIGHT</b>	
<b>Plain Paper (A0)</b>	0:37 (Fast Economy Model) 0:43 (Fast) 1:18 (Standard)		<b>Physical Dimensions and Weight</b>	
<b>Heavy coated paper (A0)</b>	1:40 (Fast) 2:33 (Standard)		W x D x H Main unit with stand 1285 x 885 x 1060 mm (Operation panel is not tilted up/Basket Opened) 1285 x 756 x 1060 mm (Operation panel is not tilted up/Basket Closed) 63.8 kg (including Roll Holder Set, excluding ink and print head)	
<b>MEDIA HANDLING</b>			<b>Packaged Dimensions and Weight</b>	
<b>Media Feed and Output</b>	Roll Paper : One Roll, Upper-loading, Front Output Cut Sheet : Upper-loading, Front Output (Manual feed using media locking lever)		Printer (Main unit with stand and pallet): 1462 x 1122 x 801 mm, 113kg	
<b>Media Width</b>	Roll paper: 203.2 - 917mm Cut sheet: 203.2 - 917mm		<b>WHAT'S INCLUDED</b>	
<b>Media Thickness</b>	Roll/Cut : 0.07mm - 0.8mm		<b>What's in the Box?</b>	
<b>Minimum Printable Length</b>	Roll paper: 203.2mm Cut sheet: 279.4mm		Printer, Printer Stand, 1 Print head, Power Cable, 1 Set of starter ink tanks, Installation Guide, Safety/Standard Environment leaflet, LFP Eur Address Sheet, Important Information Sheet, Stack Printer Stand Setup Guide, Notice for PosterArtist WEB	
<b>Maximum Printable Length</b>	Roll paper: 18 m (Varies according to the OS and application) Cut sheet: 1.6 m		<b>Software Included</b>	
<b>Maximum Media Roll Diameter</b>	150 mm		Software available as Download from Web	
<b>Media Core Size</b>	Internal diameter of roll core: 2"/3"		<b>OPTIONS</b>	
<b>Margins Recommended area</b>	Roll paper: Top: 20mm, Bottom: 3mm, Side: 3mm Cut sheet (AppleAirPrint): Top: 20mm, Bottom: 31mm, Side: 3mm Cut sheet (Others): Top: 20mm, Bottom: 20mm, Side: 3mm		<b>Optional Items</b>	
			2"/3" Roll Holder: RH2-35 IC Card Reader Holder (Installed by): RA-02	
			<b>CONSUMABLES</b>	
			<b>User Replaceable Items</b>	
			Ink Tank: M: PFI-32i(300ml) / PFI-12i(130ml), MBK/BK/C/Y: PFI-320(300ml) / PFI-120(130ml) Print Head: PF-06 Cutter Blade: CT-08 Maintenance Cartridge: MC-31	

<sup>1</sup> EPEAT Gold registered in the U.S.

#### Disclaimer

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ®: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.



Canon Inc.  
canon.com

Canon Europe  
canon-europe.com

English edition  
© Canon Europa N.V., 2023