Large Format Print Solutions Ideal for Production, Posters, and Display Graphics Applications

iPF9400S

you can

The imagePROGRAF iPF9400S is a 60", 8-colour pigment inkjet large format printer, which delivers maximum productivity and large, high quality images.

60 INCH

2,400 X 1.200 DP

LUCIA EX 8 COLOURS

"HOT SWAP" INK TANKS


250GB HDD

PHOTOSHOP PLUG-IN

BORDERLESS PRINTING

INBUILT COLOUR CALIBRATION

A0 GLOSS 3.2 MINS



iPF9400S

Key features

- Canon's innovative 8-colour pigment inkjet system with image processing technology
- Wide colour gamut, smooth gradation, deep dark tones, and sharp blacks with reduced bronzing
- Compatible with ICC profile-based colour-management systems and works seamlessly with third-party RIP applications
- Built-in 250GB hard disk, which enables highly efficient printing of complex jobs
- Enhanced Print Plug-In for Photoshop:
 - Support for Adobe CMM and Proof printing
 - Easy to create "Gallery Wrap"
 - Colour variation print for effective colour adjustment
 - Advanced Grayscale setting

- Maximise productivity "Hot Swap" ink tanks of 330ml or 700m, changeable during production
- Track the cost of each job using the built-in cost management software, allowing you to calculate ROI
- Built in colour calibration
- Borderless printing up to 60"





Specifications:imagePROGRAF iPF9400S

PRINTER MODEL	imagePROGRAF iPF9400S
TECHNOLOGY	·
Printer Type	8 Colour - 60"/1524mm
Print Technology	Canon Inkjet on demand 6 colours integrated type (6 chips per print head x 2 print heads)
Number of Nozzles	Total: 30,720 - MBK/BK/M/Y: 2,560 nozzles for each colour C/PC/PM/GY: 5,120 nozzles for each colour
Print Resolution	2,400 x 1,200dpi
Nozzle Pitch	1,200 x 2 includes non-firing nozzle detection and compensation system
Ink Droplet Size	4 Picoliter per colour
Ink Capacity	Bundled Starter Ink: 330ml Sales Ink: 330ml and 700ml
Ink Type	Pigment Ink: LUCIA EX-8-colour ink BK, MBK, C, M, Y, PC, PM, GY
Printing Speed (A0 Roll, Full Colour Image)	Plain Paper: 1.0 min (Fast Economy mode) / 3.2min (Standard mode) Coated Paper: 1.7min (Fast mode) / 3.2min (Standard mode) Glossy Photo Paper: 3.2min (Fast mode) / 4.9min (Standard mode)
OS Compatibility	Windows XP/Server 2003/Server 2008/Vista/7 (32/64bit), Macintosh OSX 10.5.8-10.7.x
Printer Languages	GARO (Graphic Arts language with Raster Operations)
Standard Interfaces	USB 2.0 High-Speed Ethernet 10/100/1000 Base-T/TX
Standard Memory	640 MB
Hard Drive	250 GB
OPERATION PANEL	
Display	Large LCD: 160 x 128 dots, Key x 13, LED x 5
Language on Operation Panel	US-English, Japanese
Displayable Language on LCD	US-English, French, German, Italian, Spanish, Chinese (Simplified), Korean, Russian, Japanese (Kanji)
PAPER HANDLING	
Media Width	Roll paper: 254mm (10inch) - 1524.0mm (60inch) Cut sheet: 203.2mm (8inch) - 1524.0mm (60inch)
Media Thickness	Roll Unit: 0.07 - 0.8mm Front Loading Manual feed: 0.07 - 0.8mm
Minimum Printable	203.2mm (8inch)
Length Maximum Printable	Roll Paper: 18 m (Varies according to the OS and application)
Length	Cut Sheet: 1.6m
Margins (Top, Bottom, Sides)	Recommended Area: Roll paper: Top: 20mm, Bottom: 5mm, Side: 5mm Cut sheet: Top: 20mm, Bottom: 23mm, Side: 5mm
	Printable Area: Roll paper: Top: 5mm, Bottom: 5mm, Side: 5mm Roll paper borderless print: Top: 0mm, Bottom: 0mm, Side: 0mm Cut sheet: Top: 5mm, Bottom: 23mm, Side: 5mm
Maximum Media Roll	
Diameter	150.0 mm
Diameter Paper Feed Method	150.0 mm Roll Paper: One Roll (front loading [front operation possible]) Cut Sheet: 1sheet front loading and front output
Paper Feed Method	Roll Paper: One Roll (front loading [front operation possible]) Cut Sheet: 1sheet front loading and front output
Paper Feed Method Media Feed Capacity Borderless Printing	Roll Paper: One Roll (front loading [front operation possible]) Cut Sheet: 1sheet front loading and front output Manual Feed: 1 Sheet, Roll Feed: 1 Roll 515 mm (JIS B2), 1, 030 mm (JIS B0), 594 mm (JSO A1), 841 mm (JSO A0),
Paper Feed Method Media Feed Capacity Borderless Printing Width (Roll Only) DIMENSIONS	Roll Paper: One Roll (front loading [front operation possible]) Cut Sheet: 1sheet front loading and front output Manual Feed: 1 Sheet, Roll Feed: 1 Roll 515 mm (JIS B2), 1, 030 mm (JIS B0), 594 mm (JSO A1), 841 mm (JSO A0),

PRINTER MODEL	imagePROGRAF iPF9400S
POWER AND OPERATING REQUIREMENTS	
Power Supply	AC 100 - 240 V (50-60 Hz)
Power Consumption	Operation: 190W or less Power off (standby): 0.5 W or less (In compliance with ErP Directive Lot.6)
Operating Environment	Temperature: 15 - 30°C, Humidity: 10 - 80 % (Condensation free)
Noise Level (Approx.)	Operation: Approx. 52 dB Standby: 35 dB or less Acoustic power: 6.8 Bels Based on ISO 7779
Regulations	Europe: CE mark Germany: TUV, Russia: Gost-R, Other Countries: CB Certification
Environment Certificates	ENERGY STAR (WW), RoHS directive, IT ECO Declaration (Europe), WEEE, ErP Lot 6 (Europe)
OPTIONS	
Basket	BU-01
Roll Holder Set	RH2-64 (2-inch core roll holder with 3-inch paper tube attachment and borderless print spacer)
CONSUMABLES	
Print Head	PF-05
Ink Tank	PFI-306 (330ml): BK, MBK, C, M, Y, PC, PM, GY PFI-706 (700ml): BK, MBK, C, M, Y, PC, PM, GY
Cutter Blade	CT-06
Maintenance Cartridge	MC-08



Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and *: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

 $Can on \, recommends \, you \, use \, Can on \, Media \, for \, the \, best \, results. \, Please \, check \, media \, (paper) \, compatibility \, list \, to \, see \, which \, variety \, of \, paper/media \, is \, recommended.$

Genuine Canon ink cartridges are developed together with Canon large format printers as an important part of the large format printer printing system. Advanced technologies achieved by our research and development activities are incorporated into these ink cartridges. For optimum performance of Canon large format printers, Canon recommends use of genuine Canon ink cartridges.











Canon Inc.

Canon Europe

canon-europe.com

09/12/v1 UK English edition 0170W808 © Canon Europa N.V., 2012 Canon (UK) Ltd

Woodhatch Reigate Surrey RH2 8BF Telephone no 01737 220000 Facsimile 01737 220022 canon.co.uk Canon Ireland

3006 Lake Drive Citywest, Saggart Co.Dublin, Ireland Telephone No: 01 2052400 Facsimile No: 01 2052525 canon.ie