



## imagePROGRAF PRO-2600

# WHERE YOUR VISION BECOMES TIMELESS PRECISION

Transform photographic skills and client demands into tangible art lasts for a lifetime, with exceptional clarity and precision. For any photographer or print service provider committed to their craft, it's not just a printer – it's a source of confidence, empowering you to realise artistic potential in each print.

- Premium image quality**  
 Deliver print perfection with exceptional colour gradation for striking photography and fine art pieces. The cutting-edge 12-colour LUCIA PRO II ink set<sup>1</sup> with Chroma Optimiser, it enhances dark density and produces deeper blacks with precision
- Increased durability**  
 Future-proof your art with the imagePROGRAF PRO-2600. Improve image robustness with high scratch resistant ink and preserve your work with better light fastness using high light-resistance pigment ink for 200 years<sup>2</sup>. Revel in unrivalled durability and set the benchmark for print longevity
- Seamless workflows**  
 Transform printing workflows with easier media handling and simplified settings. Enhance efficiency with dual rolls, auto media loading, practical interior LED light and roll media size indicator. With new print head monitoring function and auto alignment adjustment, masterpieces are created without image deterioration
- Improved sustainability**  
 Protect the environment by using less power during operation and power-off. The imagePROGRAF PRO-2600 is EPEAT Gold rated<sup>3</sup> and its packaging is free from expanded polystyrene

<sup>1</sup>Eleven out of the twelve inks are newly developed. The matte black ink is the same as the one used by the imagePROGRAF GP-2000/4000.

<sup>2</sup>When using Canon Photo Paper Pro Platinum. Predicted value calculated in accordance with the indoor light resistance test method and life evaluation criteria of the digital colour photographic print image preservation evaluation method (JEITA CP-3901B) published by JEITA (Japan Electronics and Information Technology Industries Association).

<sup>3</sup>EPEAT Gold registered in the U.S..

# Canon

# TECHNICAL SPECIFICATIONS

# imagePROGRAF PRO-2600

|   |  |  |  |
|---|--|--|--|
| <b>PRINTER TECHNOLOGY</b>                       | 12 Colours 24"   | <b>Margins Printable area</b>                | Roll paper: Top: 3mm, Bottom: 3mm, Side: 3mm<br>Roll paper (borderless): Top: 0mm, Bottom: 0mm, Side: 0mm<br>Cut sheet: Top: 3mm, Bottom: 12.7mm, Side: 3mm  |
| <b>Printer Type</b>                             | Canon Bubblejet on Demand 12 colours integrated type (12 chips per print head x 1 print head)  | <b>Media Feed Capacity</b>                   | Roll Paper: Two rolls. Automatic switching is possible.<br>Roll Paper, Cut Sheet: Manual switching is possible<br>Cut Sheet: 1 sheet   |
| <b>Print Technology</b>                         | 2,400 x 1,200 dpi  | <b>Media Take-Up Roll Unit</b>               | Dual direction roll take up unit allowing print surface to be wound inside or outside of the roll  |
| <b>Print Resolution</b>                         | 18,432 nozzles (1536 nozzles x 12 colours)   | <b>Borderless Printing Width (Roll Only)</b> | [Recommended] 515mm (JIS B2), 594mm (ISO A1), 10", 14", 17", 24"<br>[Printable] 257mm (JIS B4), 297mm (ISO A3), 329mm (ISO A3+), 420mm (ISO A2), 6", 8", 12", 15", 16", 18", 20", 22", 300mm, 500mm, 600mm<br>Other than above, free size borderless printing is supported on only roll paper by user definition |
| <b>Number of Nozzles</b>                        | ±0.1% or less  | <b>Maximum number of delivered prints</b>    | Standard position - 1 sheet<br>Flat position: A2 landscape, glossy paper less than 10 sheets, coated paper less than 20 sheets (excludes strong curled condition)  |
| <b>Line Accuracy</b>                            | User adjustments necessary. Printing environment and media must match those used for the adjustments.  | <b>POWER AND OPERATING REQUIREMENTS</b>      |  |
| <b>Nozzle Pitch</b>                             | 600 dpi x 2 includes Non-firing nozzle detection and compensation system   | <b>Power Supply</b>                          | AC 100-240V (50-60Hz)  |
| <b>Ink Droplet Size</b>                         | minimum 4pl per colour   | <b>Power Consumption</b>                     | Operation: 85W or less<br>Sleep mode: 2.2W or less<br>Default setting for the time to enter the Sleep mode: Approx. 5 minutes<br>Power off: 0.1W or less   |
| <b>Ink Capacity</b>                             | Bundled Starter Ink: 1920ml (160ml for each colour)<br>Sales Ink: 160ml / 330ml / 700ml  | <b>Operating Environment</b>                 | Temperature: 15-30°C, Humidity: 10-80% RH (no dew condensation)<br>Operation: Approx. 46dB(A) (Measured based on ISO7779 Photo Glossy Paper HG/Standard/24")<br>Standby: 35 dB(A) or less<br>Operation: 6.4 Bels or less (Measured based on ISO7779 Photo Glossy Paper HG/Standard/24")                          |
| <b>Ink Type</b>                                 | Pigment inks : 12 colours (Matte Black, Photo Black, Cyan, Magenta, Yellow, Grey, Photo Cyan, Photo Magenta, Photo Grey, Red, Blue, Chroma Optimiser)  | <b>Acoustic Noise (Power/Pressure)</b>       | CE mark, UKCA mark<br>CB certification, EPEAT GOLD <sup>2</sup>  |
| <b>OS Compatibility</b>                         | 32 Bit: Windows 7, Windows 8.1, Windows 10<br>64 Bit: Windows 7, Windows 8.1, Windows 10, Windows 11, Windows Server 2008R2, 2012, 2012R2, 2016, 2019, 2022<br>Apple Macintosh: macOS 10.15.7-macOS 13                                   | <b>Regulations</b>                           |  |
| <b>Others supported job submission protocol</b> | Apple AirPrint   | <b>Environment Certificates</b>              |  |
| <b>Printer Languages</b>                        | PDF (Ver.1.7), JPEG (Ver. JFIF 1.02)   | <b>DIMENSIONS AND WEIGHT</b>                 |  |
| <b>Standard Interfaces</b>                      | USB A Port: USB Memory (Direct Print) for PDF/JPEG files<br>USB B Port: Hi-Speed USB<br>Ethernet: IEEE802.3ab(1000base-T), IEEE802.3u(10BASE-TX)/IEEE802.3 (10BASE-T)<br>Wireless LAN <sup>1</sup> : IEEE802.11n/IEEE802.11g/IEEE802.11b | <b>Physical Dimensions and Weight</b>        | W x D x H<br>Main unit + Stand<br>110×984×1168 mm (Basket Opened)<br>110×766×1168 mm (Basket Closed)<br>102kg (including Roll Holder Set, excluding ink and print head)  |
| <b>MEMORY</b>                                   |  | <b>Packaged Dimensions and Weight</b>        | Printer (Main unit with pallet): 1324 x 912 x 1139mm, 157kg<br>Roll unit: 1244 x 562 x 461 mm, 26kg  |
| <b>Standard Memory</b>                          | 3GB  | <b>WHAT'S INCLUDED</b>                       |  |
| <b>Expansion slot : No</b>                      |  | <b>What's in the Box?</b>                    | Printer, 1 Print head, Power Cable, 1 Set of starter ink tanks, Installation Guide, Safety/Standard Environment leaflet, LFP Eur Address Sheet, Important Information Sheet, Stack Printer Stand Setup Guide, Notice for PosterArtist WEB  |
| <b>Hard Drive</b>                               | 500 GB (Encrypted HDD)   | <b>Software Included</b>                     | Software available as Download from Web  |
| <b>PRINTING SPEED</b>                           | Plain paper (A1):<br>0:58 (Fast)<br>1:38 (Standard)  | <b>OPTIONS</b>                               |  |
|   | Coated paper (A1)<br>1:38 (Standard)<br>3:11 (High Quality)  | <b>Optional Items</b>                        | 2"/3" Roll Holder: RH2-29<br>Roll Unit: RU-23  |
|   | Glossy Photo Paper (A1)<br>3:11 (Standard)<br>5:02 (High Quality)  | <b>CONSUMABLES</b>                           |  |
| <b>MEDIA HANDLING</b>                           |  | <b>User Replaceable Items</b>                | Ink Tank: MBK: PFI-2100(160ml)/PFI-2300(330ml)<br>/PFI-2700(700ml)<br>Others:PFI-3100(160ml)/PFI-3300(330ml)<br>/PFI-3700(700ml)<br>Print Head: PF-10<br>Cutter Blade: CT-07<br>Maintenance Cartridge: MC-30   |
| <b>Media Feed and Output</b>                    | Upper Roll Paper : One Roll, Upper-loading, Front Output<br>Lower Roll Paper: One Roll, Front-loading, Front Output<br>Cut Sheet : Upper-loading, Front Output<br>(Manual feed using media locking lever)                                |  |  |
| <b>Media Width</b>                              | Roll paper: 152.4 - 610mm<br>Cut sheet: 152.4 - 610mm  |  |  |
| <b>Media Thickness</b>                          | Roll/Cut : 0.07mm - 0.8mm  |  |  |
| <b>Minimum Printable Length</b>                 | Roll paper: 101.6mm (Cross and canvas paper: 200mm)<br>Cut sheet: 203.2mm  |  |  |
| <b>Maximum Printable Length</b>                 | Roll paper : 18m (varies according to the OS and application)<br>Cut sheet : 1.6m  |  |  |
| <b>Maximum Media Roll Diameter</b>              | 170mm  |  |  |
| <b>Media Core Size</b>                          | Internal diameter of roll core: 2"/3"  |  |  |
| <b>Margins Recommended area</b>                 | Roll paper: Top: 20mm, Bottom: 3mm, Side: 3mm<br>Cut sheet: Top: 20mm, Bottom: 20mm, Side: 3mm   |  |  |

<sup>1</sup> Please refer to user manual how to activate/deactivate the wireless LAN.

<sup>2</sup> EPEAT Gold registered in the U.S.

#### Disclaimer

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ®: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.



Canon Inc.  
canon.com

Canon Europe  
canon-europe.com

English edition  
© Canon Europa N.V., 2024