




HP Everyday Satin Poster Paper



The HP large format printing system—the complete solution

HP large format printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide uncompromising image quality, reliability, and consistency—with every print.



Produce cost-effective, high-quality posters

Deliver cost-effective, high-quality images

Expand your applications and help expand your profitability with this cost-effective poster paper. HP Everyday Satin Poster Paper offers vivid colors and crisp text for high-quality posters. Save time with longer rolls for increased productivity.

Recyclable,¹ FSC®-certified paper²

Produce vivid colors and crisp text and graphics on this recyclable,¹ FSC®-certified paper² that's available in a range of sizes.

See reliable results, consistent performance

Optimize your everyday printing with this economical paper's reliable, trouble-free performance designed to deliver consistent image quality and excellent handling.

Target customers	Applications	Benefits
Print service providers	Trade show and event displays	Cost-effective poster paper
	POP and retail displays	Bright-white surface, vivid colors, and crisp text
	Photo-realistic posters	Slightly textured for high-end retail advertising
		Production printing with fast dry time, longer rolls, and easy handling
		Satin finish for minimal glare or hot spots
		High opacity, minimal show-through
		Recyclable through commonly available programs ¹
		FSC®-certified paper ²

Technical specifications



HP Everyday Satin Poster Paper
For the latest ICC profiles/paper presets, please visit [HPLFMedia.com/paperpresets](https://hplfmedia.com/paperpresets).

Ink compatibility	Compatible with Original HP Latex Inks; also solvent, low-solvent, and UV-curable inks			
Weight	195 g/m² per ISO 536 Test Method			
Thickness	190 microns/7.5 mil per ISO 534 Test Method			
Opacity	>98% per TAPPI T-425 Test Method			
Brightness	>90 per TAPPI T-452 Test Method			
Whiteness	>120 per ASTM E313 Test Method			
Finish	Satin			
Operating temperature	15 to 100° C / 59 to 212° F			
Operating humidity	20 to 80% RH			
Dry time	Instant dry			
Water resistance	Moderately water resistant with Original HP 831 and 873/836 Latex Inks³			
Lamination	Hot or cold lamination; can be laminated with many commercially available laminate films⁴			
Shelf life	2 years, unopened in original packaging			
Storage temperature	0 to 40° C / 32 to 104° F			
Storage humidity	5 to 95% RH			
Environmental	Recyclable through commonly available programs; ¹ FSC®-certified paper²			
Country of origin	Product of France			
Ordering information	Product numbers	Roll sizes	UPC codes	Region
	A47FRA	914 mm x 80 m (36 in x 262 ft)	848412028362	Europe, Middle East, and Africa
	A47FSA	1372 mm x 80 m (54 in x 262 ft)	848412028379	Europe, Middle East, and Africa
	A47FTA	1524 mm x 80 m (60 in x 262 ft)	848412028386	Europe, Middle East, and Africa
Warranty	HP large format printing materials are free from defects in materials and workmanship. For warranty statement, please see HPLFMedia.com/hp/MediaWarranties . To obtain warranty service, please contact Brand Management Group customer support at HPLFMedia.com/hp/en/contactus .			

¹ Can be recycled through commonly available recycling programs.
² HP has a policy for offering Forest Stewardship Council® (FSC®)-certified papers that are sourced from FSC®-certified forests and other controlled sources. BMG trademark license code FSC®-C115319, see fsc.org. HP trademark license code FSC®-C017543, see fsc.org. Not all FSC®-certified products are available in all regions.
³ Performance varies based on printer and print profile. Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more information, see: [HPLFMedia.com/printpermanence](https://hplfmedia.com/printpermanence).
⁴ Based on testing prints produced with Original HP Latex Inks using a 3-mil vinyl film laminate that contains a water-based acrylic pressure-sensitive adhesive, a 3-mil vinyl film laminate that contains a solvent acrylic pressure-sensitive adhesive, and a 3-mil polyester film that contains a low melt copolymer blended ethylene vinyl acetate (EVA) thermal-adhesive system. Films without the above-mentioned formulations may not be compatible.



For detailed information on the HP large format printing materials portfolio and to order, see [HPLFMedia.com](https://hplfmedia.com).

