




HP Everyday Adhesive Matte Polypropylene, 2 Pack



The HP Designjet printing system—the complete solution

HP Designjet printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide reliable, consistent results with every print.



High-quality prints for your day-to-day production

Produce eye-catching displays

See outstanding image quality. Work with the wide color gamut and smooth transitions delivered by this matte polypropylene material and produce quality prints from line drawings to photo-quality POP displays.

Gain efficiency

Help keep your production process moving smoothly. This easy-to-use film features a permanent self adhesive for secure, reliable mounting.

Make the versatility of this material work for you

ICC profiles help you get the right color, right away. Take advantage of compatibility with HP dye and pigment inks. Offer over 50 years unlaminated indoor display permanence,¹ on this versatile, easy-to-use printing material.

¹ With Original HP 771 Vivid Photo Inks, Original HP 91 Photo Inks, or Original HP 70 Photo Inks on the HP Designjet Z3200 Photo Printer series. Display permanence rating for interior displays/away from direct sunlight, under glass by HP Image Permanence Lab and/or by Wilhelm Imaging Research, Inc. on a range of HP media. For more information, see globalBMG.com/hp/t/printpermanence.

² Requires 2-inch spindle for compatibility with the HP Designjet L25500 and L26500 Printer series.

Target customers	Applications	Benefits
Print service providers	POP and retail displays	Outstanding image quality for day-to-day production
Retail store in-house printing	Trade show and event displays	Instant dry time
Event designers	Temporary exhibitions	A permanent self-adhesive for secure, reliable mounting
Advertising agencies	Architecture competitions	Compatible with both HP dye- and pigment-based inks
Geographic Information Systems (GIS) Government (printing self-adhesive maps)		50+ years unlaminated indoor display permanence on HP Designjet Z-series printers ¹

Broad HP Designjet printer compatibility²



Technical specifications

Order online or call

01905 454 598



HP Everyday Adhesive Matte Polypropylene, 2 Pack

For the latest ICC/media profiles and a variety of resources to help you get the most out of your printer and HP large format printing materials, please visit globalBMG.com/hp/.

Weight (without liner)	120 g/m ² per ISO 536 Test Method																									
Weight (with liner)	168 g/m ² per ISO 536 Test Method																									
Thickness (without liner)	180 microns/7.1 mil per ISO 534 Test Method																									
Thickness (with liner)	215 microns/8.5 mil per ISO 534 Test Method																									
Opacity (with liner)	Greater than 96% per TAPPI T-425 and ISO 2471 Test Methods																									
Brightness (with liner)	101% per ISO 2470 Test Method																									
Whiteness (without liner)	Greater than 120 per ISO 11476 Test Method																									
Whiteness (with liner)	150 per ISO 11475 Test Method																									
Finish	Matte																									
Operating temperature	15 to 35° C / 59 to 95° F																									
Operating humidity	20 to 80% RH																									
Display permanence (Indoor home or office)	50+ years unlaminated with Original HP 771 Vivid Photo Inks, Original HP 91 Photo Inks, or Original HP 70 Photo Inks on the HP Designjet Z3200 Photo Printer series ³																									
Water resistance	Moderately water resistant with Original HP 771 Vivid Photo Inks, Original HP 91 Photo Inks, or Original HP 70 Photo Inks on the HP Designjet Z3200 Photo Printer series; lamination recommended with Original HP dye inks ⁴																									
Dry time	Less than 2 minutes (at 23° C, 50% RH)																									
Lamination	Yes																									
Shelf life	2 years, unopened in original packaging																									
Storage temperature	15 to 35° C / 59 to 95° F																									
Storage humidity	15 to 30% RH																									
Country of origin	Product of China																									
Ordering information	<table border="1"> <thead> <tr> <th>Product numbers</th> <th>Quantity</th> <th>Roll sizes</th> <th>UPC Codes</th> <th>Region</th> </tr> </thead> <tbody> <tr> <td>COF18A⁵</td> <td>2 Pack</td> <td>610 mm x 22,9 m (24 in x 75 ft)</td> <td>848412012934</td> <td>Worldwide</td> </tr> <tr> <td>COF19A⁵</td> <td>2 Pack</td> <td>914 mm x 22,9 m (36 in x 75 ft)</td> <td>848412012941</td> <td>Worldwide</td> </tr> <tr> <td>COF20A⁵</td> <td>2 Pack</td> <td>1067 mm x 22,9 m (42 in x 75 ft)</td> <td>848412012958</td> <td>Worldwide</td> </tr> <tr> <td>COF22A⁵</td> <td>2 Pack</td> <td>1524 mm x 22,9 m (60 in x 75 ft)</td> <td>848412012965</td> <td>Worldwide</td> </tr> </tbody> </table>	Product numbers	Quantity	Roll sizes	UPC Codes	Region	COF18A ⁵	2 Pack	610 mm x 22,9 m (24 in x 75 ft)	848412012934	Worldwide	COF19A ⁵	2 Pack	914 mm x 22,9 m (36 in x 75 ft)	848412012941	Worldwide	COF20A ⁵	2 Pack	1067 mm x 22,9 m (42 in x 75 ft)	848412012958	Worldwide	COF22A ⁵	2 Pack	1524 mm x 22,9 m (60 in x 75 ft)	848412012965	Worldwide
Product numbers	Quantity	Roll sizes	UPC Codes	Region																						
COF18A ⁵	2 Pack	610 mm x 22,9 m (24 in x 75 ft)	848412012934	Worldwide																						
COF19A ⁵	2 Pack	914 mm x 22,9 m (36 in x 75 ft)	848412012941	Worldwide																						
COF20A ⁵	2 Pack	1067 mm x 22,9 m (42 in x 75 ft)	848412012958	Worldwide																						
COF22A ⁵	2 Pack	1524 mm x 22,9 m (60 in x 75 ft)	848412012965	Worldwide																						
Warranty	HP large format printing materials are free from defects in materials and workmanship. For warranty statement please see globalBMG.com/hp/MediaWarranties .																									

³ Display permanence rating for interior displays/away from direct sunlight, under glass by HP Image Permanence Lab and/or by Wilhelm Imaging Research, Inc. on a range of HP media. For more information, see globalBMG.com/hp/t/printpermanence.

⁴ Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more information, see globalBMG.com/hp/t/printpermanence.

⁵ Requires 2-inch spindle for compatibility with the HP Latex 260.

For detailed information on the HP large format printing materials portfolio and to order, see globalBMG.com/hp

