


# HP Gloss Poster Paper, 3-in Core for HP PageWide Technology





# The HP large format printing system—the complete solution

HP PageWide XL printers, Original HP PageWide XL pigment inks and printheads, and Original HP printing materials are designed to work together as a system to provide reliable, consistent results with every print.



In North America and Asia (including Japan), recyclable in consumer collection systems that can accept mixed paper (may not be recyclable in your area); in Europe recyclable in consumer collection systems that accept liquid packaging.

## **Produce attention-getting gloss prints**

#### Deliver excellent image quality

HP Gloss Poster Paper, 3-in Core for HP PageWide Technology provides vibrant color and excellent image quality. Produce point-of-sale (POS) posters at breakthrough speeds.

#### **Expand your applications**

Offer a wide array of graphic applications including POS posters and GIS maps.

#### Maintain a smooth workflow and high productivity

Move smoothly and rapidly through post-print processing with this fast-dry poster paper. Experience reliable and trouble-free performance.

Target customers	Applications	Benefits	
Print service providers	POS posters	High-production printing	
Retail store in-house printing	Presentations	Vibrant poster image quality	
	GIS maps	Fast dry time for easy handling	
		Recyclable through commonly available programs <sup>1</sup>	



### **Technical specifications**



#### HP Gloss Poster Paper, 3-in Core for HP PageWide Technology

For the latest ICC profiles/paper presets, please visit <u>HPLFMedia.com/paperpresets</u>.

	100 / 3 100 534	C.T. (14.1)					
Weight	190 g/m² per ISO 538	190 g/m² per ISO 536 Test Method					
Ink technology	Original HP PageWid	Original HP PageWide XL pigment inks					
Thickness	185 microns/7.3 mil	185 microns/7.3 mil per ISO 534 Test Method					
Opacity	96% per TAPPI T-425	96% per TAPPI T-425 Test Method					
Brightness	92% per TAPPI T-452	92% per TAPPI T-452 om-87 Test Method					
Whiteness	120 per ISO 11476 Te	120 per ISO 11476 Test Method					
Finish	Gloss	Gloss					
Operating temperature	10 to 30° C / 50 to 86	10 to 30° C / 50 to 86° F					
Operating humidity	30 to 65% RH	30 to 65% RH					
Dry time	Immediate (at 23°C,	Immediate (at 23°C, 50% RH)					
Shelf life	1 year, unopened in	1 year, unopened in original packaging					
Storage temperature	10 to 30° C / 50 to 86	10 to 30° C / 50 to 86° F					
Storage humidity	30 to 65% RH	30 to 65% RH					
Recyclability	accept mixed paper (	In North America and Asia (including Japan), recyclable in consumer collection systems that can accept mixed paper (may not be recyclable in your area); in Europe recyclable in consumer collection systems that accept liquid packaging					
Country of origin	Product of Germany	Product of Germany					
Ordering information	Product numbers	Roll sizes	UPC codes	Region			
	L5Q08A	1016 mm x 61 m (40 in x 200 ft)	848412016192	Worldwide			
Warranty	statement please se	HP large format printing materials are free from defects in materials and workmanship. For warranty statement please see <a href="https://example.com/hp/MediaWarranties">HPLFMedia.com/hp/en/contactus</a> . contact Brand Management Group customer support at <a href="https://example.com/hp/en/contactus">HPLFMedia.com/hp/en/contactus</a> .					



For detailed information on the HP large format printing materials portfolio and to order, visit HPLFMedia.com

© 2015 Hewlett-Packard Development Company. © 2015 Brand Management Group. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP and BMG shall not be liable for technical or editorial errors or omissions contained herein.

