
www.plot-it.co.uk



The HP large format printing system—the complete solution

HP large format printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide reliable, consistent results with every print.



- B1, M1, and NFPA701 approved fire certifications.
- This product does not contain substances listed as SVHC (155) per Annex XIV of the EU REACH directive published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Declaration published at HP Printing Products and Consumable Supplies. Logo source: Copyright European Chemicals Agency.
- Rub resistance testing by HP Image Permanence Lab according to ASTM F1319.

Produce brilliant, high-impact displays with this competitively priced, wrinkle-resistant light textile

Find new profit potential with this reasonably priced light fabric

Create high-impact displays and banners for events and retail POP. This economically priced polyester fabric produces brilliant prints that resist creases and wrinkles. Offer custom work and optimize the cost advantages of this easy-to-use, knitted polyester fabric. And discover new profit potential with this versatile, lightweight textile.

Reassure your clients with environmental and fire certifications

Differentiate your offering with a compelling alternative to PVC for banners and displays. This flame-resistant¹ light fabric is REACH compliant² and OEKO-TEX certified⁴, to help you and your customers meet high health and safety standards.

See excellent ink saturation for vibrant image quality

Deliver crisp image quality and bright colors with the wide color gamut produced by HP Latex Inks.

Target customers	Applications	Benefits		
Print service providers	Trade show and event displays	Recyclable ⁷ alternative to traditional banner and display materials		
	POP/POS and retail displays	Wide color gamut		
	Banners	Wrinkle and crease resistant		
	Interior decorations	An alternative to PVC for banners and displays		
	Pop-up/roll-up displays	Flame resistant ¹		
		REACH compliant ²		
		Rub- and scratch-resistant prints ³		
		OEKO-TEX certified ⁴		

Technical specifications Order online or call 01905 454 598





HP Light Fabric

For the latest ICC/paper presets, please visit <u>HPLFMedia.com/hp/paperpresets</u>.

Weight	218 g/m² per ISO 536 Test Method, (6.2 oz)					
Thickness	381 microns/15 mil per ISO 534 Test Method					
Tensile strength	MD > 400 N/25 mm / CD > 1100 N/25 mm per ASTM D 882-02					
Finish	Matte					
Brightness	92% per TAPPI T-452 Test Method					
Whiteness	138 per ISO 11475 Test Method					
Opacity	Greater than 75% per TAPPI T-425 Test Method					
Water resistance	Water resistant with HP Latex Inks⁵					
Wind orientation	lmage side in					
Finishing	Recommend cutting with a hot knife					
Operating temperature	15 to 35° C / 59 to 95° F					
Operating humidity	30 to 80% RH					
Flame resistance	B1, M1, and NFPA701 approved fire certifications ¹					
Dry time	Instant dry					
Shelf life	1 year, unopened in original packaging					
Storage temperature	5 to 40° C / 41 to 104° F					
Storage humidity	5 to 95% RH					
Environmental	REACH compliant ^{2,} OEKO-TEX certified ⁴					
Country of origin	Product of Germany					
Ordering information	Product numbers	Roll sizes	UPC codes	Region		
	J7U83A	1067 mm x 45,7 m (42 in x 150 ft)	848412015065	Worldwide		
	J7U84A	1372 mm x 45,7 m (54 in x 150 ft)	848412015072	Worldwide		
	J7U85A	1524 mm x 45,7 m (60 in x 150 ft)	848412015089	Worldwide		
Warranty	HP large format printing materials are free from defects in materials and workmanship. For warranty statement, please see HPLFMedia.com/hp/MediaWarranties . To obtain warranty service, please contact BMG customer support.					

- 4 HP Light Fabric is certified according to OEKO-TEX® Standard 100, which is a globally uniform testing and certification system for textile raw materials, intermediate, and end products at all stages of production. Tested for emissions of volatile organic compounds and chemical residues such as pesticides, allergy-inducing dyestuffs, or tin-organic compounds.
- 5 Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more information, see HPLFMedia.com/hp/printpermanence.
- It is necessary to use the take-up reel with the HP Latex 210 and platen cover (B2W90A) with the HP Latex 210, 260 and 280 Printers. The platen cover is included with the HP Latex 360 Printer.
- ⁷ HP Large Format Media take-back program availability varies. Recycling programs may not exist in your area. See hp.com/recycle for details.





For detailed information on the HP large format printing materials portfolio and to order, visit HPLFMedia.com

© 2018 Hewlett-Packard Development Company. © 2018 Brand Management Group. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP and BMG shall not be liable for technical or editorial errors or omissions contained herein.



HP is a registered trademark of Hewlett-Packard Company and is used by Brand Management Group on license from Hewlett-Packard Company.