



HP PageWide XL Pro Stacker for HP PageWide XL Pro



Stack jobs as quickly as you print them with the HP PageWide XL Pro Stacker



Adaptability and Flexibility

- Stack sheets and boards up to 10 mm thick, sizes 102 x 122 cm (40 x 48 in), and weights 70 to 1.050 g/m² (19 to 115 lbs).
- Print mixed jobs from rolls of different materials and sizes, and stack the output neatly into the Pro Stacker.

Productive workflow from start to finish

- Designed specifically to support the high-speed performance of HP PageWide XL Pro printers.
- Enables productivity from beginning to end for HP PageWide XL Pro printing of paper, card stock, and boards.

WWW.PLOT-IT.CO.UK
Order online or call
01905 454598

Fully integrated for reliable operation

- Experience reliable operation with bi-directional communication between the printer and your Pro Stacker.
- Monitor the status of your Pro Stacker via the front panel, HP SmartStream, or certified RIP solution.

Technical specifications

General	Capacity	Up to 50mm (1.98 in) total thickness
	Stack sheet and boards	Up to 10 mm thick, sizes 102 x 122 cm (40 x 48 in), and weights 70 to 420/m ² (19 to 115 lbs)
	Max page size	102x122cm (40x48in)
	Media weight	70 to 420 g/m ² (19 to 115 lb)
Paper handling	Sheet/Board stacking	Face up
	Max stacker speed	Maximum speed supported by the printer *
	Min stacker speed	Minimum speed supported by the printer
	Max sheet size supported on the stacker table	40-inch wide sheets (E size portrait)
	Min sheet/board size supported	A4**
	Paper set supported	Full board and cut sheet set supported by the printer and paper set with 3-inch roll core ???
Connectivity		Same as HCS
Dimensions	Dimensions with packaging	1.50x1.2x0.87 m (59.1x47.2x34.3 in)
	Dimensions without packaging	1430x1280 m (56.3x50.4 in) height adjustable according to printer version
Weight	Weight with packaging	171 kg / 377 lb
	Weight without packaging	Empty: 120 kg (265 lb) / With full Tray: 233 kg (514 lb)
Environmental	Operating temperature	5 to 40 °C (41 to 104 °F)
	Recommended temperature	15 to 35 °C (59 to 95 °F)
	Operating humidity	20 to 80% RH, depending on media type
Acoustic	Sound pressure	Idle <20 dB(A); Operating 66 dB(A) (Fast mode)
	Sound power (printing)	Idle <3.5 B(A); Operating ≤8.3 B(A) (Fast Mode)
Power	Consumption	36.57 W (maximum normal load) / 8.30 W (only motors working)
	Voltage range	32 Vdc, 5 A
Certification	Safety	IEC 60950-a+A1+A2 and IEC 62368-1 2nd ed, compliant; USA and Canada (CSA listed)
	Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI)
	Environmental	CE marking (including RoHS, WEEE, REACH). In compliance with WW RoHS materials restriction requirements in China, Korea, India, Vietnam, Turkey, Serbia and Ukraine
Warranty		90 days
Compatibility		HP PageWide XL Pro 5200 MFP HP PageWide XL Pro 8200 MFP HP PageWide XL Pro 10000 Printer

Ordering information

Product 8SB04A HP PageWide XL Pro Stacker



- 1 Roof to help keep flexible media flat
- 2 HP PageWide XL Pro Stacker with up to 5cm total stacking weight
- 3 Adjustable height
- 4 Lever adjusting stacker's thickness to media

© Copyright 2021 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Adobe, Acrobat, Illustrator, Photoshop, and PostScript are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries. Intel is a trademark of Intel Corporation in the U.S. and other countries. Windows is a U.S. registered trademark of Microsoft Corporation.