

Window Film Clear Graphic Art Range IFA 100

Product Description

BCrystal clear polyester film designed for value orientated, high volume print shops using eco-solvent printers.

Features

- Crystal Clear
- Eco-Solvent, Latex and UV Ink Compatible
- Specialist Wet Cling Coating
- Apply to Inside of Window

Applications

- Short Term Window Graphics
- Point of Sale Promotions

Basic Weight (gsm)	135		
Film Thickness (Microns)	125	Film Thickness (Inches)	0.007
Base Material	Polyester		
Coating Type	Eco-Solvent Gloss		
Surface Texture	Smooth		
Whiteness (CIE)	Not Applicable		
Brightness (TAPPI)	Not Applicable		
OBA Content	No		
Opacity (%)	0		
pH	Not Applicable		
Recyclable	Yes		
Ink Type	Eco Solvent, UV and Latex		
Notes	For profiles please contact your rip vendor.		

Sheets	N/A		
Rolls (25m Length, 3"Core)	60", 42", 30"		

Additional Sizes are available on request, subject to order quantity.

Handling and Storage

- All digital Fine Art Papers and Canvases are fragile and need to be handled with extreme care. Try not to touch the surface of the paper, always hold the paper by the edges and wear cotton gloves if necessary.
- Return unused material to the original box and only store finished prints in archival quality packaging. If mounting or framing, use only archive grade tapes and glues.
- After printing, leave prints open to the air to fully dry (24 hours is recommended). Do not stack prints on top of each other straight away.
- Using a giclée varnish or spray will help protect your print from damage, effects of UV light and environmental attack.

Conditions of Use

- The recommended climate for storage of all papers is 15-20°C, relative humidity of 40-60%. Always store in original packaging, out of direct sunlight and protected from moisture.
- Do not exceed temperatures of 82°C (180°F) when dry mounting.

All recommendations are for your guidance only. These are subject to our test criteria, which remain subject to change without prior notice.