

Toner

CrystalPoint

(eco) Solvent

UVgel / UV

Latex

IJM672 PVC Film, Satin, M2

310 µm

Product Description

An M2-certified, satin coated and tear resistant rigid PVC film with a waterfast coating.

Physical Properties

Weight film	420 g/m ²	ISO 536	Opacity	> 99 %	ISO 2471
Thickness film	310 µm	ISO 534	Gloss 60°	10	ISO 2813

*All values listed are target values

Applications/features

Indoor signs and promotions
Displays, Pop-up displays
Outdoor signage

Suitable for UVgel and UV curable inks
Tear resistant hard PVC base
Cardboard-like touch
High image definition and color brilliance
Waterfast prints
M2 certified (fire retardant)

Available Widths (mm)

3"core	914	1372								
--------	-----	------	--	--	--	--	--	--	--	--

Refer for our current offering to www.canon-europe.com/mediaguide

Storage Conditions

Shelf life: 2 years. Temperature 10-30°C, Relative Humidity 35-65%
Repack opened rolls when not in use.

Print Conditions

Best results are obtained between 15-25°C and 30-65% RH.

Environment, Health & Safety

No Material Safety Data Sheet required.

Lamination Compatibility

Cold	Warm	Hot	Cold: pressure sensitive Warm: heat activated: 85°C - 95°C Hot: heat activated: 105°C -130°C
yes	no	no	

Outdoor Use

Suited for short to media term outdoor use.

Colour Profiles

Canon develops high-quality colour profiles for media / ink / printer / RIP combinations.
Check availability of profiles for your printer on www.canon-europe.com/mediaguide

Processing Guidelines

Printing guidelines

Allow material to adapt to room conditions for 24 hours before printing. It is recommended to handle the media with cotton gloves. Make sure that the media comes not into contact with grease, oil, silicon, and dirt to avoid printing defects.

Load the media with care in the printers. Incorrect loading can cause skewing or creasing. Use a take-up device to prevent wrinkling.

It is recommended to calibrate the printer before printing and to make a test print. Print results will vary for different printer/ink combinations.

Canon media profiles include recommended settings for ink restrictions and printer parameters. Depending on fluctuations in environment, printer, ink, media and applications, printer parameters may have to be adjusted slightly, in order to obtain the best results. Heaters should be set to a maximum of 35°C to avoid waves/wrinkling.

For high-speed production printing, using an external drying unit is recommended.

IJM672 is also compatible with UV curable inks.

However, UV lamps should be run on low performance settings to avoid high temperatures.

Printing on flatbed is recommended.

Application guidelines

The film can be easily mounted with and removed from double-sided adhesive tape without any problems.

IJM672 can be used outdoor without lamination. However, we recommend protecting its surface if it is subject to abrasion or any other mechanical influences. The film has good lamination characteristics.

Standard disclaimer:

All specifications subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon Inc.
canon.com

Canon Europe
canon-europe.com

English edition 0116

© Canon Europa N.V., 2019

The Canon logo is displayed in its characteristic red color and bold, sans-serif font at the bottom right corner of the page.