

Toner
CrystalPoint™
WaterBased Ink
UV Curable
Latex

LFM054 Red Label Paper - PEFC

75 g/m²

Product Description

Quality paper with low chlorine content and high whiteness. Excellent for use where the quality of your documents must reflect the image of your work and organisation.

Physical Properties

Weight	75 g/m ²	ISO 536	Thickness	102 µm	ISO 534
Bulk	1,36 cm ³ /g	ISO 534	Roughness	220 ml/min	ISO 8791-2 Bendtsen
CIE Whiteness	164,0 %	ISO 11475	Opacity	93 %	ISO 2471

All values listed are target values

Applications/features

High quality drawings and posters

ISO 9706 standard for permanence
EMAS and ISO 14001 certified
PEFC Chain-of-Custody
EU Ecolabel

Available Widths (mm)

3" core	210	297	420	594	620	841	914	1067		
---------	-----	-----	-----	-----	-----	-----	-----	------	--	--

Refer for our current offering to www.canon-europe.com/mediaguide

Storage Conditions

Shelf life: 2 years, Temperature 21°C, Relative Humidity 50%.
Repack opened rolls when not in use. Allow material to adapt to room conditions for 24 hours before printing.

Print Conditions

Best results are obtained between 20-27°C and 30-60% RH.

Environment, Health & Safety

No Material Safety Data Sheet required. Paper waste suitable for recycling.

Lamination Compatibility

Cold	Warm	Hot
yes	yes	yes

Cold: pressure sensitive
Warm: heat activated: 85°C - 95°C
Hot: heat activated: 105°C -130°C

Outdoor Use

Developed for indoor use.

Colour Profiles

Canon develops high-quality colour profiles for media / ink / printer / RIP combinations.
Check availability of profiles for your printer on www.canon-europe.com/mediaguide

Environmental Certification



WWW.PLOT-IT.CO.UK

Order online or call

01905 454598

Canon

Processing Guidelines

Printing guidelines

Allow material to adapt to room conditions for 24 hours before printing.

It is recommended to handle the media with cotton gloves. Make sure that the media does not come into contact with grease, oil, silicon, and dirt to avoid printing defects.

Insert media with care in the printers. Incorrect loading can cause skewing or creasing. Allow material to adapt to room conditions for 24 hours before printing. It is recommended to calibrate the printer before printing and to make a test print. Print results will vary for different printers.

Ink/toner restrictions and printer settings have to be set for specific printers to obtain the best results. Canon colour profiles include recommended ink restrictions and printer settings for Canon supported printers.

Application guidelines

When laminating CrystalPoint® prints pressure sensitive laminates are recommended.

A laminator with soft rubber rollers is preferred. For optimal results temperature should be set between 55-60 °C.

Standard disclaimer:
All specifications subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

