

Toner
CrystalPoint™
Water
UV Curable
Latex

LFM411 Fluorescent Paper

95 g/m²

Product Description

Colour coated, single-side fluorescent paper in yellow, pink, orange or green. The pigments are heat-resistant and free of formaldehydes.

Physical Properties

Thickness	110 µm	ISO 534	Stiffness MD/CD	57 / 25 mN	DIN 53864
Weight	90 g/m ²	ISO 536	Smoothness Bekk FS/BS	50 / 25 s	DIN 53107

All values listed are target values

Applications/features

POS posters Strong fluorescent colours
Events, Signage

Available Widths (mm)

3" core yellow	841
3" core green	841
3" core pink	841
3" core orange	841

Refer for our current offering to www.canon-europe.com/mediaguide

Storage Conditions

Temperature 10-20°C, Relative Humidity 20-50%
Repack opened rolls when not in use.

Print Conditions

Best results are obtained between 10-30°C and 40-70% RH.

Environment, Health & Safety

No Material Safety Data Sheet required.

Lamination Compatibility

Cold	Warm	Hot	Cold: pressure sensitive Warm: heat activated: 85°C - 95°C Hot: heat activated: 105°C -130°C
yes	yes	yes	

Outdoor Use

This coloured paper is not suited for outdoor use.

Colour Profiles

Canon develops high-quality colour profiles for media / ink / printer / RIP combinations. Check availability of profiles for your printer on www.canon-europe.com/mediaguide

Order online or call
01905 454 598

Printing guidelines

LFM411 is compatible with ColorWave printers with Océ CrystalPoint™ technology. Do not use the CDT/stacker when printing LFM411.

It is recommended to handle the media with cotton gloves. Make sure that the media does not come into contact with grease, oil, silicon, and dirt to avoid printing defects. Insert media with care in the printers. Incorrect loading can cause skewing or creasing. Allow material to adapt to room conditions for 24 hours before printing. It is recommended to calibrate the printer before printing and to make a test print. Print results will vary for different printers.

Ink/toner restrictions and printer settings have to be set for specific printers to obtain the best results. Canon colour profiles include recommended ink restrictions and printer settings for Canon supported printers.



WWW.PLOT-IT.CO.UK

Standard disclaimer:

All specifications subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.