







THE ULTIMATE ENTRY LEVEL LAMINATOR





THE ULTIMATE ENTRY LEVEL LAMINATOR

Combines innovation and high performance at a very economical price.

The Laylam series is in fact designed and built to adapt to the widest range of applications, from vehicle wrapping to interior decoration and paper converting, to expand to the most diverse applications of visual communication and sign-making.

Thanks to the use of pneumatic technology, the Laylam series of laminators reduces machine setup and preparation times and therefore the need to employ specialized personnel.

Contrary to laminators with electric pressure technology, the possibility of error in calculating the thickness is eliminated.

Models available include cold (50°C) and hot (120°C) roller systems.

MAIN FEATURES

Eco-friendly

The air pressure system requires much lower energy consumption compared to electric motors.

Self-adaptive

Independent pistons automatically adjust to different thicknesses and the manages the flatness defects of the substrate. The rollers adapt to the surface in real time.

Flexible

Pre-set the pressure applied to each substrate whilst retaining the option to manually adjust pressure during the laminating process.

OPTIONS / ACCESSORIES

- Roll holder with clutch
- Rewinder roll

Available in the following versions:

- Laylam 50°C
- Laylam 120°C



Datasheet	1650	
Dimensions	215x45xh140 cm	
Max working width	1650 mm	
Max speed	6 m/min	
Max laminating thickness	30 mm	
Depth table included	450 mm	
Height working table	920 mm	
Net weight	200 kg	
Electrical requirements	230v - 50Hz / 110v - 60Hz	
Power consumption	7,5A - 1800W	

* The manufacturers reserves the right to change technical and aesthetical specifications without notice.