HP Non-woven Durable Linen Wall Paper





The HP large format printing system—the complete solution

HP large format printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide reliable, consistent results with every print.



What is EN233?

EN233 is a European Wallcovering Standard that specifies requirements for cleanability and light fastness, and gives a designated marking system. The standardization is intended to ensure consistency throughout the industry.

Produce innovative, eye-catching PVC-free¹ wall murals

Be productive—non-woven durable wall paper prints are easy to install and remove

Help your customers define interiors with durable, colourful, creative wall decorations that last—with scrub- and scratch-resistant performance. Easy to install with standard wall glue only, this wallpaper produces seamless results, and it is both easy to apply and dry strippable. Thanks to the special backing that doesn't expand when wet, soaking the paper prior to hanging is no longer required; the paste can be applied directly to the wall. This feature provides long-lasting, durable adherence to the substrate.

Set your business apart with environmental certifications

A PVC-free¹ alternative that is easier to dispose of than most PVC-based substrates. The non-woven base paper is FSC®-certified² and the wall paper is flame resistant,³ REACH compliant,⁴ and carries the CE certification.⁵

Boldly define interior spaces—see the ColorPRO difference

See high-impact graphics with an extended range of colours. Engineered with ColorPRO Technology to deliver colour excellence, this digital wall decoration solution from HP delivers professional quality and striking results.

Target customers	Applications	Benefits	
Print service providers	Wall murals	Compliance with international wallcovering industry standards	Environmental and health certifications
Interior designers	Wall cut-outs	EN233 extra washability rating (wave 3)	REACH compliant ⁴
	Creative design applications	Works with common primers, pastes, finishing, and installation methods	PVC-free ¹ alternative, easier to dispose of than most PVC-based substrates
			FSC®-certified non-woven base paper²
			Class A rated flame-spread performance material ³
			Carries the CE certification ⁵





Technical specifications

HP Non-woven Durable Linen Wall Paper

For the latest ICC profiles/paper presets, please visit HPLFMedia.com/hp/paperpresets.

	Tor the latest icc p	Tof the latest ice profiles/paper presets, please visit <u>The Fredia Contributor paper presets</u> .				
Ink technology	Compatible with Original HP Latex Inks and UV-curable inks					
Weight	200 g/m² per TAPPI T-410 Test Method					
Thickness	330 microns/13 mil per TAPPI T-411 Test Method					
Finish	Matte					
Operating temperature	15 to 35° C / 59 to 95° F					
Operating humidity	30 to 80% RH					
Display permanence (Commercial in-window)	1.5+ years, unlaminated with HP Latex Inks ⁶					
Display permanence (Indoor home or office)	20+ years, away from direct sun with HP Latex Inks					
Water resistance	Water resistant with HP Latex Inks ⁷					
Flame resistance	Class A ³					
Dry time	Instant dry					
Shelf life	2 years, unopened in original packaging					
Storage temperature	10 to 40° C / 50 to 104° F					
Storage humidity	20 to 80% RH					
Country of origin	Product of China					
Ordering information	Product numbers	Roll sizes	UPC codes	Region		
	2Q240A	1372 mm x 45 m (54 in x 147 ft)	848412025941	Europe, Middle East, and Africa		
	2Q241A	1372 mm x 120 m (54 in x 393 ft)	848412025934	Europe, Middle East, and Africa		
Warranty	nty HP large format printing materials are free from defects in materials and workmanship. statement, please see <u>HPLFMedia.com/hp/MediaWarranties</u> . To obtain warranty service, BMG customer support at <u>HPLFMedia.com/hp/en/contactus</u> .					

- 1 Chemical analysis demonstrated elemental chlorine to be at or below 200 ppm. Presence of chlorine is attributed to residual chlorine used in the papermaking process, and not due to the presence of PVC.
- ² BMG trademark license code FSC®-C115319, see <u>fsc.org</u>. HP trademark license code FSC®-C017543, see <u>fsc.org</u>. Not all FSC®-certified products are available in all regions. For information about HP large format printing materials, please visit <u>HPLFMedia.com</u>.
- ³ Class A tested to ASTM E84-13a for burning characteristics, rated per section 803.1.1 of the International Building Code.
- As of the date of this document, this product does not contain any of the chemicals on the EU's Candidate List for Authorization (otherwise known as Substances of Very High Concern) in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Article 33 Declaration published at HP Printing Products and Consumable Supplies.
- ⁵ Self-declared according to European Standard EN15102.
- ⁶ Interior in-window display ratings by HP Image Permanence Lab on a range of HP media. HP predictions based on test data under Xenon-Arc illuminant—calculation assumes 6,000 Lux/12 hr day. For more information, see <u>HPLFMedia.com/hp/printpermanence</u>.
- Performance varies based on printer and print profile. Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more information, see HPLFMedia.com/hp/printpermanence.











For detailed information on the HP large format printing materials portfolio and to order, visit HPLFMedia.com

© 2021 HP Development Company, L.P. © 2021 Brand Management Group. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP and BMG shall not be liable for technical or editorial errors or omissions contained herein.

