

Photo Papers Speciality

Photo Metallic Gloss 260gsm OLM71



Description:

This Neutral white RC paper has a pearlescent finish with a smooth gloss microporous coating to give excellent colour saturation, gamut and D-max.

Applications include; Photography, portrait printing, posters and exhibiton printing.

Weight (GSM)	260
Base Material	Resin Coated
Coating Type	Microporous Gloss
Surface Texture	Smooth pearlescant gloss
Thickness (Microns / inches)	267 / 0.011
Whiteness (CIE)	80
Brightness (TAPPI)	82
OBA content	No
pH	7.5-9.5
Sheets Size: Availability / sheets per box	DIN A4 / A3 / A3+ / A2 - 50 sheets (US sizes available on request)
Roll Size: Availability / Length / Core size	17" (432mm) / 24" (610mm) / 44" (1118mm) - 30m - 3" core
Printer/Ink Compatibility	Compatible with all commercial thermal and piezo inkjet printers using water-based dye and pigment-based inks such as Epson, Canon and Hewlett-Packard
Recommended printer Settings	Photo black inks with generic media setting of 'Premium Photo Gloss' / 'Premium Photo paper Semi-matte' or similar. ICC colour profiles are available from the website.

Directions for Use:

Paper Handling:

- Avoid touching the coated surface of the paper before and after printing, and wear cotton gloves if necessary.
- Avoid exposure to high temperatures, high levels of humidity and moisture. These factors can affect the drying time of some OlmecTM products.

Paper Storage:

- Remove prints from the tray after printing; do not allow them to be stacked.
- Prints should be allowed to dry in air, preferably left uncovered for 24 hours to allow the residual liquid from the inks to evaporate.
- In cases where stacking is unavoidable, a paper interleaf should be placed between each print.

Conditions of Use:

- Where possible, all paper should be stored and used within the following range of environmental conditions:
Temperature = 10° - 35°Centigrade
Relative Humidity = 30% - 80%
- Unused paper should be stored in its original packaging, out of direct sunlight under normal climatic conditions.

All recommendations and product indications are for your guidance, and are subject to our test criteria.