



NON-WOVEN DESIGN2WALL UV 150

matt 2500, 150 g/m²

Special non-woven wallpaper with natural, structured surface for UV-curing inks.

Advantages

- Dimensional stability
- High dry/wet strength
- PVC-free
- Suitable for use with various wall adhesive techniques
- Removal when dry
- Low wet stretching
- Optimal drying shrinkage
- Good lightfastness
- FSC® certified
- Flame-retardant c-s1, d0



Technologies



Properties



- Dimensionally stable
- Double seam cut

General tips

To maintain the high quality of this wallpaper, it should be stored and converted in a climate of 30 – 65 % relative humidity and at a temperature of 10 – 30 °C (50 – 86 °F).

Physical data

Name	Value	Norm
Weight [g/m ²]	150	ISO 536
Thickness (paper) [µm]	320	ISO 534
ISO Brightness [%]	88	ISO 2470- 1
Opacity [%]	90	ISO 2471
Tensile strength MD [N/15mm]	148	ISO 1924- 3/2/300
Tensile strength CD [N/15mm]	94	ISO 1924- 3/2/300
Wet tensile strength MD [N/15mm]	47	ISO 3781
Wet elongation CD (Fenchel) [%]	0.1	A 10-011/27
Water absorbency (Cobb) [g/m ²]	18	ISO 535

The values stated above are only for orientation. Before using our print media please check its compatibility for your printer and the intended application. We cannot be held responsible for any mistakes resulting from technically modified printers and/ or inks. Product design changes to our products technical developments may be carried out without prior notice.