



NON-WOVEN DESIGN2WALL SOL 195

matt 2512, 195 g/m²

High quality, non-woven wallpaper coated with a solvent ink receptive layer, which offers a good colour gamut and high scratch resistance. Due to the properties of this wallpaper, no additional protection is needed and it can be hung with standard non-woven wallpaper paste.

Advantages

- The coating and prints are water-resistant - no liquid lamination required
- Quick dry
- Smooth surface
- Wide gamut and high colour rendering
- High opacity for good coverage
- High dimensional stability and wet strength resistance
- Can be applied with standard paste for non-woven wallpaper
- Covers small cracks
- Easy to remove
- PVC-free
- FSC® certified



Technologies



Properties



- Dimensionally stable
- Double seam cut

General tips

To maintain the high quality of this fleece, it should be stored and converted in a climate of 30 – 65 % relative humidity and at temperatures of 10 – 30 °C (50 – 86 °F).

After pasting the wall with a standard wallpaper paste, the wallpaper can be hung just like all other fleece wallpapers. Thanks to its structure, it is easy to remove again and requires no additional protection.

Physical data

Name	Value	Norm
Weight [g/m ²]	195	ISO 536
Thickness (paper) [µm]	340	ISO 534
Whiteness, CIE D65/10°	75	ISO 11475
Opacity [%]	90	ISO 2471
Chromaticity (D65/10°)	L* 97 a* -0.5 b* 3.5	DIN 6174

The values stated above are only for orientation. Before using our print media please check its compatibility for your printer and the intended application. We cannot be held responsible for any mistakes resulting from technically modified printers and/ or inks. Product design changes to our products technical developments may be carried out without prior notice.