

01905 454 598 Order online or call





SYNTISOL PP FILM EASYTACK 330

satin 3529, 330 µm

Universal, polypropylene film with easy to use low-tack adhesive

SyntiSOL PP Film EasyTack is a self-adhesive polypropylene film with a look and feel similar to paper. This durable and tear resistant film for printing with solvent and UV inks is ideal for lettering and signage of all kinds, e.g. at POS, for sales promotions or for advertising displays. The removable EasyTack adhesive allows easy and bubble-free application and easy removal from all smooth surfaces without leaving residues. The material is suitable for medium-term indoor applications, as well as short-term usage in outdoor scenarios.

Advantages

- · Brilliant colour reproduction
- EasyTack easy to apply, easily removable
- · Splashproof prints for short-term outdoor applications
- · Edge tear resistant
- Suitable for use on cutter plotters

General tips

The converting and storage should take place in a climate of 35 to 65% to relative humidity at temperatures of 10 to 30°C. Keep the product in the original packaging (cardboard box and PE bag). Cotton gloves should be worn when handling InkJet coated materials to avoid fingerprints.

Physical data

Name	Value	Norm
Thickness (film) [µm]	330	ISO 4593
Test conditions	23°C / 50% R.F.	
Weight [g/m²]	280	ISO 536
Adhesion strength on glass (48h) [N/25mm]	~ 0.5	FINAT No.1, 22°C
Whiteness, CIE D65/2°	82	ISO 11476

Technologies





Properties





your printer and the intended application. We cannot be held responsible for any mistakes resulting from technically modified printers and/ or inks. Product design changes to our products technical developments may be carried out without prior notice.

The values stated above are only for orientation. Before using our print media please check its compatibility for

12.09.2018 Page 1/1

www.plot-it.co.uk