



# CLEAR SOL WETCLING FILM 125

glossy 3550, 125 µm

Transparent film for window display advertising, with easy water application

A clear, coated polyester film for solvent, latex or UV printing for indoor application. The film has been especially developed for temporary window display advertising. It adheres to glass and other smooth surfaces. The special coating developed for this product enables easy application – only using soapy water (no liner required). The printed side of the film is applied directly to the moistened window or smooth surface. The film can be removed without leaving residues even after several months. Thanks to its exceptional transparency, this film is also suitable for many other applications, e.g. for glass signage elements or as normal cling film.

## Advantages

- Excellent colour brilliance
- Very high transparency
- Can be used as clear film or as a cling film
- Easy to apply – easy to remove

## General tips

The converting and storage should take place in a climate from 35 to 65% to relative humidity at temperatures of 10 to 30°C. Keep the product in the original packaging (cardboard box and PE bag). It is always recommended that cotton gloves be used when handling InkJet coated materials to avoid fingerprints.

## Physical data

Name	Value	Norm
Thickness (film) [µm]	125	ISO 4593
Weight [g/m <sup>2</sup> ]	170	ISO 536

## Technologies



## Properties



The values stated above are only for orientation. Before using our print media please check its compatibility for your printer and the intended application. We cannot be held responsible for any mistakes resulting from technical changes in the printing process and with printing components. Product design changes to our products technical developments may be carried out without prior notice.