



EXHIBITION STAND
CONSTRUCTION / POS /
EVENTS

ROLL-UP FILM PLUS 210 SB MATT AQ

matt 3597, 210 µm

Roll-Up Film Plus 210 SB Matt AQ (3597) was designed to produce roll-up and display graphics with waterbased and latex inks. The matt coating on the front ensures excellent scratch resistance and a high print quality and brilliant colour reproduction. The tear-resistant polypropylene/polyester composite guarantees problem-free processing and provides a high level of opacity thanks to the matt silver back. Besides it shows good flatness and constructional stability in roll-up systems. Due to its excellent price-performance ratio, Roll-Up Film Plus 210 SB Matt AQ is the ideal choice for the production of high volume products for short to mid-term use.

Advantages

- Brilliant colour reproduction
- Anti-reflective, matt surface
- Matt, silver back for high opacity
- Good flatness for short to mid-term use
- Tear-resistant
- Scratch-resistant surface and reverse side

General tips

We recommend that prints are left 24 hours before further processing. The product should be stored in the original packaging at room temperatures of 15 – 25 °C, with a relative humidity of 40-60%.

Physical data

Name	Value	Norm
Thickness (film) [µm]	210	ISO 4593
Weight [g/m ²]	165	ISO 536
Whiteness, CIE D65/2°	123	ISO 11476
Opacity [%]	99.6	ISO 2471
Gloss (60°)	2.6	ISO 2813

Technologies



Properties

