

# Order online or call





## I UNA CANVAS PRIME SATIN AQ

satin 3948, 340 g/m<sup>2</sup>

High quality, satin canvas with a natural structure for professional photo prints and artistic reproduction.

Luna Canvas Prime Satin AQ is a high quality artistic canvas on a cotton / polyester blend base with a coating for waterbased inks. The 2:1 weave offers a light irregular structure, which makes it optimal for artistic and Fine Art prints. The absence of brighteners preserve the natural colouring and leads to a higher light stability and longer lifespan.

The satin finish coating enables photorealistic prints with excellent colours and deep, rich blacks. The material shows no white-scoring and prints are splashproof.

### Advantages

- · Brilliant colour reproduction
- · Deep, rich blacks
- · Quick dry
- No white-scoring
- · Outstanding light stability
- Splashproof

#### General tips

The converting and storage should take place in a climate of 35 to 65% relative humidity at temperatures of between 10 and 30°C. Due to the natural components of the material it tends to curl when relative humidity is fairly high, which can cause print head damage. We recommend that the material is first removed from original packaging when printing commences!. After the printing process put the media back in its original packaging. Cotton gloves are always recommended when handling Inkjet coated materials to avoid fingerprints.

Use dye inks only for short-term application (2-3 weeks). The inkjet coating is waterresistant with the correct inks as shown below. The product has mainly been designed for indoor applications. For long-term applications, the use of pigmented inks is strongly recommended. The media may also be sewn and used as a banner. Attention when using cut sheets: only put one sheet into the printer feeding. For protection and to reduce the impact of dirt, physical abrasion or other environmental impact we recommend to use a protective laquer.

#### Physical data

Name	Value	Norm
Weight [g/m²]	340	ISO 536
Thickness (paper) [µm]	470	ISO 534
Weave structure	2:1	
Base	65% Polyester / 35% Cotton	

**Technologies** 



**Properties** 

Structure

The values stated above are only for orientation. Before using our print media please check its compatibility for your printer and the intended application. We cannot be held responsible for any mistakes resulting from technical changes in the printing process and with printing components. Product design changes to our products technical developments may be carried out without prior

09.10.2018 Page 1/1