

UltiMaker Factor 4

Product data sheet



Introducing the light industrial best-inclass FDM process for manufacturing tools and low-volume production of auxiliary compnents.

- New H Frame Gantry System: Improved accuracy and dimensional stability
- Process monitoring and quality insurance
- ✓ New exclusive materials
- Enhanced service packages

The UltiMaker platform



3D printers that simply work Our award-winning 3D printers are robust, reliable, and easy to use. They deliver quality parts time and again. Designed and tested to run 24/7, they allow you to achieve the results you need more quickly and easily.



Software for industry 4.0
Trusted by millions of users across 14 languages,
UltiMaker Cura integrates with any workflow through
UltiMaker Marketplace
plugins. Scale production and digital distribution with
UltiMaker Digital Factory.



Material choice unlike any
UltiMaker offers the widest
material choice on the
market. Through our Material
Alliance, choose the perfect
filament for your application
– from advanced polymers to
carbon fiber composites.



Support for your success Wherever you are in the world, UltiMaker support is close by. Our global network of service partners offer professional installation, training, and maintenance in your language and time zone.

UltiMaker Method Wash Tank specifications	
Technology	Fused deposition modeling (FDM)
Print head	
Build volume (XYZ)	30 x 240 x 300 mm
Layer resolution	
XYZ resolution	
Build speed	
Build plate	PEI-coated flexible build plate
Feeder type	
Spool bays	
Air Manager	EPA filter
Nozzle diameter	
Operating sound	
Conectivity	Wi-Fi (2.4Hz + 5GHz), LAN, USB port
Dimensions	W 800 x D 750 x H 1600 mm
Net Weight (packaging + pallet)	137 KG
Country of origin	NLD

MacOS, Windows, and Linux

Supported OS

