

## XXPMC120

## Xativa X-Press Matt Coated Paper



A FSC certified 120gsm paper with excellent colour reproduction and short drying time.

## ${\it Ideal for mono and colour CAD line drawings, architectural plans and GIS maps.}$

Produce rich colour accurate prints with this 120gsm thick bright white paper. Its enhanced coating provides quick ink absorbtion and abrasion resistance enabling you to handle the print as soon as it is completed.

And to help meet the the environmental objectives of your company and your clients this recyclable FSC certified paper supports responsible forest management worldwide.

All specifications are correct at time of print and are subject to change without notice. E&OE

| Droduct | specifications |
|---------|----------------|
| Product | Specifications |

| Product specification       | S   |   |  |
|-----------------------------|---|---|--|
| Weight                      | 117 g/m² (+/- 7 gsm) isos36   |   |  |
| Thickness                   | 142 microns (+/- 7 microns) ISO534  |   |  |
| Opacity                     | > 92% (+/-3%) DIN53146  |   |  |
| Whiteness                   | 150 (+/- 5%) ISO11475   |   |  |
| Finish                      | Matt  |   |  |
| Shade                       | L 97 (+/- 2)  |   |  |
|                             | a 3.3 (+/- 1)   |   |  |
|                             | b -13 (+/- 2)   |   |  |
| Smoothness                  | 45 (+/- 20s) isos627  |   |  |
| Stiffness md                | 6 (+/- 4mN) ISO2493   |   |  |
| Stiffness cd                | 5 (+/- 2mN) ISO2493   |   |  |
| Operating temperature       | 15 to 100 degrees centigrade  |   |  |
| Operating humidity          | 20 to 80% RH  |   |  |
| Dry time                    | Instant dry with heating (at 23 degrees centigrade, 50% RH)                           |   |  |
| Shelf time                  | 2 years, unopened in original packaging   |   |  |
| Storage temperature         | 0 to 40 degrees centigrade  |   |  |
| Storage humidity            | 5 to 95% RH   |   |  |
| Country of origin           | Product of Germany  |   |  |
| Printer / Ink Compatibility | Compatible with all aqueous based dye, pigment and UltraChrome K3 Inks from all leadi |   |  |
|                             | manufacturers such as Canon, Epson and Hewlett Packard                                |   |  |
| Lamination                  | Can be laminated with commercially available thermal and pressure sensitive films     |   |  |
| Ordering information        | Product numbers   | Roll Sizes  |  |
|                             | XXPMC120-A4   | A4 x 150 sheets   |  |
|                             | XXPMC120-A3   | A3 x 150 sheets   |  |
|                             | XXPMC120-A3+  | A3+ x 150 sheets  |  |
|                             | XXPMC120-A2   | A2 x 150 sheets   |  |
|                             | XXPMC120-17   | 432mm x 45m   |  |
|                             | XXPMC120-24-30  | 610mm x 30m   |  |
|                             | XXPMC120-24   | 610mm x 45m   |  |
|                             | XXPMC120-36   | 914mm x 45m   |  |
|                             | XXPMC120-36-90  | 914mm x 90m   |  |
|                             | XXPMC120-42   | 1067mm x 45m  |  |
|                             | XXPMC120-42-3   | 1067mm x 45m (3 inch core)                                  |  |
|                             | XXPMC120-42-90  | 1067mm x 90m  |  |
|                             | XXPMC120-54   | 1371mm x 45m  |  |
|                             | XXPMC120-60   | 1524mm x 45m  |  |
| Warranty                    | Xativa large format printing  | materials are guaranteed to meet Xativa published           |  |
|                             | specifications, to be free of r   | manufacturing flaws and defects, and are designed to resist |  |
|                             | paper jams when used corre  | ectly   |  |













WWW.PLOT-IT.CO.UK
Order online or call
01905 454598

The mark of responsible forestry